



**GUARDIAN**<sup>®</sup>

# HALO CABLE LEADING EDGE

Self-Retracting Lifeline

The Halo Class 2 Self-Retracting Lifeline is part of Guardian's strongest lineup of SRLs in the industry. This anchored Class 2 SRL is recognized throughout the industry for its superior performance. It has evolved over the years to incorporate the features workers want the most and is the go-to SRL for leading edge applications in multiple industries.

Class

**2**

Anchor above  
or below dorsal  
D-ring

**HEIGHT SAFETY.  
SIMPLIFIED.**

[guardianfall.com](http://guardianfall.com)



# HALO CABLE LEADING EDGE

Self-Retracting Lifeline



Class

2

Anchor above  
or below dorsal  
D-ring



10925

## Key features & benefits

### Swivel top connection point

Swivels 360 degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling. Double locking carabiner included.

### All metal housing

Heavy Duty & durable for long lasting use in the toughest applications

### QR code enabled labels

Easy access to product information

### Rubber lifeline stopper

Doubles as a convenient hand-grip

### Steel cable lifeline

Resists cuts and abrasions

### Guardian shock pack cover

Helps increase product longevity and protect safety labeling

### Fall-indicating swivel snap hook

Shows if SRL has been exposed to an impact

## Specifications

### User weight range (including clothing, tools, & equipment)

ANSI (LE use) | 130-310 lb

OSHA (Non-LE use) | 100-420 lb

Max. Arrest Force | 1,800 lb

Avg. Arrest Force | 1,350 lb

Materials | Aluminum, stainless steel, galvanized steel, rubber

### Non-LE use (Anchor at or above dorsal D-ring)

Max. Arresting Distance | 42 in

Max. Allowable Free Fall | Not Permitted

Min. Fall Clearance: 7 ft

### LE Use (Anchor below dorsal D-ring)

Min. Setback Distance from Edge | 0 ft

Max. Arresting Distance | 8 ft 6 in

Max. Allowable Free Fall | 5 ft

Min. Fall Clearance: 17 ft



## Declaration of conformity

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:

OSHA 1910.140 & 1926.502 | ANSI Z359.14


For more information:

+1 (800) 466 6385

info@guardianfall.com



Designed and  
tested in the  
United States



Part numbers	Description	Hook type	Length	User Weight Range
10920	Halo SRL, Cable, Class 2	Steel swivel snap hook	20'	See specifications
10922	Halo SRL, Cable, Class 2	Steel swivel snap hook	25'	See specifications
10925	Halo SRL, Cable, Class 2	Steel swivel snap hook	30'	See specifications

**Declaration of conformity**

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:  
**OSHA 1910.140 & 1926.502 | ANSI Z359.14**

For more information:

**+1 (800) 466 6385**

**info@guardianfall.com**



Designed and  
tested in the  
**United States**