



Nedo® Product Information

Medium-Duty Elevating Tripod

Retract-And-Go®
locking system



Ref.-No.	210 616-185
Min. effective height	approx. 31" / 0.80 m
Max. effective height	approx. 80" / 2.00 m
Retracted length	approx. 40" / 1.00 m
Holding screw	5/8" x 11 thread
Weight	approx. 11 lbs. / 5.10 kg
Tripod plate, Ø	4.3" / 110 mm
Telescopic section	1-fold
Adjustable column range	21" / 545 mm

Features:

- Indirect gear unit for easy handling
- Inch and mm scale on elevating column
- Circular bubble
- Strong aluminum extension legs, silver anodized
- Tripod head and plate made of aluminum, powder-coated
- Break-proof quick release levers, made of aluminum
- Brass hinge pins for extra stability
- Tripod shoes made of high-tech plastic material w/ steel points
- Slip guard
- Retract-and-go transport locking system

Suitable for:

- Rotating lasers

Technical data subject to change



Nedo®

Precise surveying and measuring

Nedo

2200 Ampere Drive · P.O. Box 99556
Louisville, KY 40269-0556

Toll-free 866-ask-nedo · 866-275-6336
Fax 502-266-5280

sales@usa.nedo.com
www.usa.nedo.com