



# Nedo® Product Information

## Heavy-Duty Elevating Tripod



<b>Ref.-No.</b>	<b>210 678-185</b>
Min. effective height	approx. 40" / 1.01 m
Max. effective height	approx. 116" / 2.94 m
Retracted length	approx. 52" / 1.32 m
Weight	approx. 7.44 kg
Tripod plate, Ø	4.3" / 110 mm
Holding screw	5/8" x 11 thread
Telescopic section	2-fold
Adjustable column range	20"/19" / 490/520 mm

### Features:

- Indirect gear unit
- Double telescope for a wide working range
- Inch and mm scale on elevating column
- Circular bubble
- Strong aluminum extension legs, silver anodized
- Tripod head and plate made of aluminum, powder-coated
- Break-proof quick release levers, made of aluminum
- Brass hinge pins for extra stability
- Combi tripod shoes for all-terrain use
- Slip guard

### Suitable for:

- Rotating lasers
- Heavy-duty rotating lasers

Technical data subject to change



# Nedo®

Precise surveying and measuring

### Nedo

2200 Ampere Drive · P.O. Box 99556  
Louisville, KY 40269-0556

Toll-free 866-ask-nedo · 866-275-6336  
Fax 502-266-5280

sales@usa.nedo.com  
www.usa.nedo.com