



EXTENDED FREE FALL LANYARD

Lanyard

The Big Boss extended free fall lanyard allows for free fall of up to 12' for workers up to 310 lbs, and can also accommodate workers up to 420 lbs for free fall up to 6'.

Unlike a traditional external shock absorbing lanyard, the Big Boss incorporates additional material in the shock absorber to allow for greater shock absorbing properties.

Always be sure to account for additional deceleration distances in your fall clearance calculation.

**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



EXTENDED FREE FALL LANYARD

Lanyard



21300

Key Features & Benefits

Clear shock pack cover

Easy inspection and lanyard longevity

Heavy-duty label cover

Prevents improper adjustment and accidental slippage

Steel snap or steel rebar hooks

Galvanized steel hooks for strength and unparalleled durability

Specifications

User weight range | 130-310 lbs (up to 12')

User weight range | 130-420 lbs (up to 6')

Materials | Polyester, nylon, & galvanized steel

Hook Options



Steel snap hook



Steel rebar hook



21302



21310

Declaration of conformity

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.3-2019. All testing is validated by a third party professional engineer.

This product is compliant with the following safety regulations:
ANSI Z359.3-2017 & Z359.13-2013 | OSHA 1910.140 & 1926.502

For more information:

+1 (800) 466 6385

info@guardianfall.com



Designed, tested,
and assembled in
the **United States**

EXTENDED FREE FALL LANYARD

Lanyard



Part numbers	Description	Leg	Hook type	Length
21300	Nylon webbing lanyard	Single	Steel snap hook	6'
21301	Nylon webbing lanyard	Single	Steel rebar hook	6'
21302	Nylon webbing lanyard	Dual	Steel snap hooks	6'
21303	Nylon webbing lanyard	Dual	Steel rebar hooks	6'
21310	Nylon webbing lanyard, 18" extension	Dual	Steel rebar hooks	6'

For more information:
+1 (800) 466 6385
info@guardianfall.com



Designed, tested,
and assembled in
the **United States**