

Cold Snap™



SHELL CONSTRUCTION

- Cold Snap Extreme™, 15-Gauge
- Red Nylon Outer Shell
- 2-Ply Thermal
- Brushed Acrylic/Polyester Inner Lining

COATING

- Black Foam PVC, Fully Coated

PERFORMANCE INFORMATION

- ANSI/ISEA 105-2016
- Cut Level A3



DESCRIPTION:

Cold Snap Xtreme™, PVC, Foam, Thermal, A3 Cut : 3915

ColdSnap Xtreme™: Two-Ply Shell: 15-Gauge, Red Nylon Outer, Brushed Acrylic Inner, Fully Coated, Black Foam PVC Coating, Fabric Overedge Cuff

CERTIFICATIONS & RATINGS:

Component Materials comply with all federal regulations for food contact. (U.S. Code of Federal Regulations, 21CFR, Parts 170-199)

APPLICATIONS:



CARE:

Wash using warm water and commercial laundry detergent. Water temperature not to exceed 50°C/122°F. Air-dry or tumble-dry with low heat.

ORDERING:

Unit of Sale: One Dozen
Packaging: 12 Prs/Polybag
Case Pack: 6 Dozen
COO: Pakistan
Available Sizes: M-2XL

Case Weight (lbs)

M	L	XL	XXL
25	26	28	30

BARCODES:

ITEM	DOZEN	CASE
3915M	796326017944	50796326017215
3915L	796326017203	50796326017949
3915XL	796326017210	50796326017956
3915XXL	796326017951	50796326011022

Corporate Headquarters:

4025 Viscount Avenue
 Memphis, TN 38118
 Phone 800.458.8763
 Fax 901.458.3343

CORE SAFETY PROTECTION
www.cordovasafety.com

West Coast Office:

433 Cheryl Lane (Dock Door 14)
 City of Industry, CA 91789
 Phone 909.590.2679
 Fax 909.590.3130