



Precise surveying and measuring



# Nedo Builders' Levels F-Series

Strong optics, rugged design and reliable



**NEDO BUILDERS'  
LEVELS F-SERIES**



**Tough!  
With metal housing**



Scope of delivery:  
Carrying case, lens cover, plumb bob,  
allen key, adjusting pin

## Nedo Builders' Levels F-Series

Nedo **F-Series** levels feature first-class optics with 24x, 28x or 32x magnification, sturdy metal housing, a top-quality magnetic-damped compensator and a modern design. Just right for use under tough conditions.

### Features:

- Automatic builders' level with 24x, 28x or 32x magnification
- Bright optics with large objective aperture
- Sturdy, reliable magnetic-damped compensator
- Sturdy metal housing
- High-contrast image
- Inspection record
- Comes with plumb bob, adjusting pin and robust case

### Nedo Builders' Levels F-Series

	F24	F28	F32
<b>Ref.-No.</b>	460 778-613	460 796-613	460 798-613
<b>Magnification</b>	24x	28x	32x
<b>Clear objective aperture</b>	30 mm	30 mm	40 mm
<b>Minimum focusing distance</b>	23.6" / 0.6 m	23.6" / 0.6 m	23.6" / 0.6 m
<b>Stadia constant</b>	100	100	100
<b>Compensator range</b>	± 15'	± 15'	± 15'
<b>Compensator setting accuracy</b>	± 0.5"	± 0.3"	± 0.3"
<b>Horizontal circle</b>	360°	360°	360°
<b>Sensitivity of circular bubble</b>	8'/0.08" / 8'/2 mm	8'/0.08" / 8'/2 mm	8'/0.08" / 8'/2 mm
<b>Accuracy 1 km Double run leveling standard Deviation</b>	± 2.5 mm	± 2.0 mm	± 1.5 mm
<b>Protection class</b>	IP 54	IP 54	IP 54
<b>Weight</b>	2.8 lbs. / 1.26 kg	2.8 lbs. / 1.26 kg	2.8 lbs. / 1.26 kg
<b>Connecting thread</b>	5/8" x 11	5/8" x 11	5/8" x 11



**Nedo** GmbH & Co. KG  
 2200 Ampere Drive · P.O. Box 99556  
 Louisville, KY 40269-0556  
 Toll-free 866-ask-nedo · 866-275-6336  
 Fax 502-266-5280  
 sales@usa.nedo.com  
 www.usa.nedo.com

Your Nedo Dealer