



Nedo® Product Information

Nedo Winkelfix

With the Nedo **Winkelfix**, measurements of angles are performed quickly, precisely and with the utmost ease. Simply place the Nedo **Winkelfix** in position and the angle can be rapidly read off from the analog display. Two integral spirit levels ensure true horizontal and vertical positioning. Thanks to its reliability, sturdiness and convenience, the Nedo **Winkelfix** has proven its value to the building trade over and over again. You too will find measuring angles easier with one of our three Winkelfix models! All Nedo Winkelfix models are supplied with a case as a standard.



Winkelfix mini



Winkelfix maxi and shorty



Degrees can be read off immediately from the analog display.
 Display graduations: $\pm 0.5^\circ$
 Measuring accuracy: $\pm 0.25^\circ$

Nedo Winkelfix

Ref.-No.	Shank length	Graduations	Measuring range	Compass points	Weight
500 101-185 shorty	12" / 305 mm	degrees	0 to 180°	no	1.5 lbs. / 0.7 kg
450 111-185 mini	17" / 430 mm	degrees	0 to 180°	no	2.0 lbs. / 0.9 kg
500 111-185 maxi	23" / 600 mm	degrees	0 to 180°	yes	2.6 lbs / 1.4 kg



All Nedo Winkelfix models are supplied with a case as a standard

Errors and omissions excepted



Precise surveying and measuring

Nedo

2200 Ampere Drive · P.O. Box 99556
 Louisville, KY 40269-0556

Toll-free 866-ask-nedo · 866-275-6336
 Fax 502-266-5280

sales@usa.nedo.com
 www.usa.nedo.com