

## **Western Enterprises**

875 Bassett Road

Westlake, OH 44145-1142 **Toll Free:** 800.783.7890

**Phone:** 440.871.2160

**Email:** <u>sales@westernenterprises.com</u> **Website:** www.westernenterprises.com

## ITEM # 615-2, UP TO 500 PSIG PRESSURE HAND-TIGHT MALE NUT

Western Hand-Tight Nuts provide for easy installation and are available in brass or with plastic grips.

- Lightweight plastic grips have labels which are color-coded for gas service.
- All brass nuts are machined to CGA specifications and designed with wrench flats.
- O-ring type nipples should always be used with hand-tight nuts.
- CGA fittings rated over 3000 PSIG do not have soft tips and final gas-tight seating requires wrench action.



## Specifications | Additional Information | Prop 65

Specifications	
Field	Industrial
Gas Service	Acetylene (POL) CGA- 510
Pressure Rating	Up to 500 psig
Material	Brass
Thread Type	Hand-Tight Male
Thread Direction	Left Hand (LH)

Additional Information	
	Five different types of nut/nipple combinations are available:
Additional Information	<ul> <li>Brass nut and nipple</li> <li>Stainless steel nut and nipple</li> <li>Nut and nipple with check</li> </ul>

Prop 65	
Warning	This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm.

• Nut and nipple recessed for

• Hand tight nut and nipple

valve

tubing