

Western Enterprises 875 Bassett Road Westlake, OH 44145-1142 Toll Free: 800.783.7890 Phone: 440.871.2160 Email: <u>sales@westernenterprises.com</u> Website: www.westernenterprises.com

ITEM # 6296, UP TO 3000 PSIG PRESSURE MALE HAND-TIGHT THREAD TYPE BRASS MATERIAL NUT

Western Hand-Tight Nuts provide for easy installation and are available in brass or with plastic grips.

- Lightweight plastic grips have labels which are color-coded for gas service.
- All brass nuts are machined to CGA specifications and designed with wrench flats.
- O-ring type nipples should always be used with hand-tight nuts.
- CGA fittings rated over 3000 PSIG do not have soft tips and final gas-tight seating requires wrench action.



Specifications | Additional Information | Prop 65 | Note

Specifications	
Field	Industrial
Gas Service	Industrial Mixtures Of Oxygen CGA-296
Pressure Rating	Up to 3000 psig
Material	Brass
Thread Type	Male Hand-Tight
Thread Direction	Right Hand (RH)
Additional Information	
	Five different types of nut/nipple combinations are available:
	Brass nut and nippleStainless steel nut and nipple

Additional Information	 Nut and nipple with check valve Nut and nipple recessed for tubing Hand tight nut and nipple
Prop 65	
Warning	This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
Note	
Note	Please note that all types may not be available for certain gas services.