Lifetime Guarantee



Thank you for purchasing this installation kit from Intellitronix. We value our customers!

INSTALLATION GUIDE

LS Engine Swap Adapter Kit – for Series 1, 2 and 3 Part Number: 8014LS

* Always disconnect the battery before attempting any electrical work on your vehicle.*



Kit Components:

- ♦ One (1) Bushing 1/8" NPT to 12 mm for water temperature sender
- ♦ One (1) Bushing 1/8" NPT to 16 mm for oil pressure sender
- ♦ One resistor for tachometer connection

INSTRUCTIONS

Note: Automotive circuit connectors are the preferred method of connecting wires. However, you may solder if you prefer.

- 1. Insert 12 mm bushing into the port located on the rear of the right side cylinder head. Then, insert temperature sender into bushing and complete wiring.
- 2. Insert 16 mm bushing into the port on the engine block, which is usually located near the oil filter. Then insert oil pressure sender into bushing and complete wiring.
- 3. If the tachometer does not work, you will need to install the enclosed resistor. It should be inserted between the green wire from the tachometer and the (red) 12v Ignition Wire.
- 4. The connections for the resistor may be soldered at each end.

Be sure to test for leaks before driving the vehicle.

www.intellitronix.com



Technical Support

Monday – Friday 9am to 5 pm EST

(440) 210-7646 support@intellitronix.com



This product carries a limited Lifetime Warranty.

This warranty is limited to replacement or repair of the unit at the discretion of Intellitronix.