

ANY SPOT®

WIRELESS PERSONAL MONITOR

AS-950

The AS-950 is easy to use. The Any Spot® WPM replaces floor wedges and the amplifiers that power them. Simply plug the ANY SPOT® into a 'monitor out' jack on the mixing console, create the desired mix, and it's ready to deliver quality sound. The AS-950 has 16 selectable UHF frequencies which can transmit in either mono or stereo.

The AS-950R (receiver) features an 50mW x 2 headphone amplifier with a standard 3.5mm (1/8") headphone output. The LCD Display and Up/Down buttons make channel selecting an easy task. The AS-950R is sure to be plenty loud for any environment. The receiver has a built-in limiter.

The AS-950T (transmitter) has two XLR/1/4" combo jacks for its inputs, stereo/mono switch & headphone output w/ volume control. The transmitter includes a single/dual rack mount kit, for mounting one unit in one rack space or mounting two transmitters side by side in one rack space.

The Any Spot® Series of Wireless Personal Monitors is a great alternative for performers who are tired of lugging around heavy and bulky floor monitors and tired of leaving a gig with ringing ears. The AS-950 allows the user to move freely around the stage and continue to hear the monitor mix.



AS-950T

- 16 Selectable UHF Frequencies
- Send a Stereo or Mono Mix to Any Number of Receivers on Stage
- Easy Setup Right Out of the Box
- XLR / 1/4" Combo Line Level Input
- Easy to Read Audio LED Indicators
- Input Level Control
- 1/4" Headphone Output with Volume Control for Easy Monitoring

AS-950R

- Built-in Limiter
- Multi-function LCD Display
- Up and Down Channel Select Buttons
- Operates on 2 AA Batteries (Alkaline or Rechargeable)
- Lightweight Titanium Driver EB4 Ear Buds Included

Band Pack System

The AS-950-4 Band Pack Systems makes it easy for any band to **Get Personal**. The system includes four receivers and one transmitter. It is designed to get the whole band wireless in one package. The AS-950-4 will allow a band to send one stereo mix to 4 individuals. Add as many additional receivers as needed.



MAKERS OF THE ORIGINAL
HOT SPOT PERSONAL MONITOR



ANY SPOT[®]

WIRELESS PERSONAL MONITOR

AS-950

Specifications:

AS-950 System

Band: UHF

Transmitter Output Level: 10 mW

Operating Range: Under Typical Conditions 200' (61m)

Note: actual range depends on RF signal absorption, reflection, interference, and battery characteristics

Audio Frequency Response: +/-3dB 50Hz~15kHz

Total Harmonic Distortion: <1% @ 1kHz

Signal to Noise: >80dBA

Maximum Deviation Range: +/-40kHz

Dynamic Range: >90dB A-weighted

Operating Temperature Range: 14°F to 122°F (-10° C to +50° C)

Note: battery characteristics may limit this range

Included Accessories: Power Supply, EB4 Ear Buds, Antenna, Single/Dual Rack Ears, Quick Start Guide

AS-950T Transmitter

Main Frame Size: EIA STANDARD 1/2U

Modulation Mode: FM Stereo Modulation

RF Output: 10 mW

Max Audio Input Level: +6dBV

Gain Adjustment Range: 40dB

Controls: Headphone Volume, Channel Up/Down, and Power Button

Audio Input: Line Level x 2, XLR/1/4" Combo Jack

XLR Input: Impedance balanced

Pin: 1 Ground (cable shield)

Pin: 2 Audio +

Pin: 3 No Audio -

Dimensions: 1.73" x 8.34" x 3.77" (44 x 212 x 96 mm)(HxWxD)

Weight: 19.75 oz (560 g)

Power Supplied By: 12-18 V DC at 300mA supplied by external power supply

AS-950R Body Pack Receiver

Audio Output Level: 50mW x 2

Sensitivity: -94dBm for 30dB

Stereo Separation: 40dB (at 1kHz)

Output Connector: 1/8" (3.5mm) Stereo Earphone Connector

Controls: Volume, Channel Up/Down

Indicators: Multi-function LCD, LOW Battery, RF LED

Dimensions: 3.54" x 2.51" x 0.9" (90 x 64 x 23 mm)(HxWxD)

Weight: 3.35 oz (95 g) without batteries

Power Supplied By: 2 (AA) size alkaline or rechargeable batteries

Battery Life: Up to 12 hours (alkaline)



AS-950T Transmitter



BACK VIEW



EB4 Standard Ear Buds

AS-950R

FREQUENCY CODES

CODE N 518 - 542 MHz

CODE P2 470 - 489 MHz



Specifications subject to change without notice.



MAKERS OF THE ORIGINAL
HOT SPOT PERSONAL MONITOR

601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 www.galaxyaudio.com
Distributed in Canada by Audio Distributors International (ADI) 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada
450.449.8177 FAX 450.449.8180

V20180823