



## ELECTRICAL SPECIFICATIONS

Frequency Range: 2.4-2.5/4.9-5.85 GHz  
Gain: 4 / 2 dBi  
Polarization: 3 Horizontal—3 Vertical  
Horizontal Beamwidth: 90°/90°  
Vertical Beamwidth: 80°/90°  
VSWR: < 2.0:1

Isolation: >20 dB  
Impedance: 50 Ω  
Lightning Protection: DC Grounded  
Max Input Power: 100W per port



## MECHANICAL SPECIFICATIONS

Dimensions: 8.1" x 7" x 1.8" (205.7x178x45.7mm)  
Weight: 1.2 lb (0.59 kg)  
Mounting: Threaded Bolt w/ Nut or  
Articulating Wall/Pole Mount (included)  
Installation Hole Diameter: 1" (25mm)  
Pole Mount Diameter: 2" (50.8mm)

Radome Material: ASA  
Connector: N-Style  
Number of Leads: 6  
Cable Length: 36" (914 mm)  
Cable Type: ATS-195



## ENVIRONMENTAL SPECIFICATIONS


Installation Environment: Indoor/Outdoor  
Operating Temperature: -40 to 149°F (-40 to 65°C)  
Wind Velocity: 130 mph (209 km/h)  
IP Rating: IP66

## WARRANTY

2 Year Limited Warranty



## HORIZONTAL



## VERTICAL

