



CUSB3-AP*

USB 3.0/3.1 Gen 1 Javelin™ Active Optical Plenum Cable

FEATURES

- Plenum Rated
- Data transfer rates of upto 5 Gigabits per second
- Offers fiber-optic noise immunity
- No additional power supply required
- Supports all USB 3.0 (USB 3.1 Gen 1) devices
- Thin and flexible with bend radius of 0.3 inch
- Plug and Play – no driver installation required



DESCRIPTION

The CUSB3-AP cables are members of Hall Technologies' Javelin™ family of active optical video and USB cables. The CUSB3-AP cables are used to extend USB 3.0 (USB 3.1 Gen1) Super-Speed signals at data rates of up to 5 Gbps. They support transparent extension of USB 3.1 Gen1 and are compatible with all USB 3.0 devices including 4K USB 3.0 cameras and USB 3.0 memory devices. They are offered at standard lengths of 15, 30, and 50 meters (50, 100 , and 164 ft).

The cables are light-weight and are constructed using a hybrid of fiber and copper. Fiber optics offer high immunity to EMI and RFI noise for trouble free operation. The cable uses minimal power and does not require any additional power supply. The USB host connection provides 5v power for operation and the cable sends 5v via its copper wires to the remote (device) end. The cables are constructed using Plenum (CMP) Rated jacket material to ensure compliance with modern building codes. The small cable ends can be easily pulled through most conduits (pulling sock is recommended).

CUSB3-AP cables are compatible with virtually all USB 3.0 and 3.1 Gen1 devices, and are a perfect solution for extending 4K videoconferencing cameras, video capture, docking stations, and other high-speed data communications. They are not recommended for use with USB 2.0 or 1.1 devices. For use with USB 2.0 or 1.1 Hall Technologies offers Special Hubs with USB 2.0/1.1-to-USB3.0 Transaction Translators that convert USB 2.0 traffic to USB 3.0 so that they can be extended using the CUSB3-AP cables.

Note that the CUSB-AP cables only extend USB 3.0 signals.



Performance Characteristics	Input Output Available Lengths USB Standards Bandwidth	Male USB 3.0 Type A Female USB 3.0 Type A CUSB3-AP-15 15 meters (50 ft) CUSB3-AP-30 30 meters (100 ft) CUSB3-AP-50 50 meters (164 ft) USB 3.0 or USB 3.1 Gen 1 5 Gbps max
Electrical Characteristics	Supply Voltage Supply Current Power consumption	Powered from USB 5v pin Nominal: 5v (operating range: 4.7v ~ 5.3v) Damage will occur if 5v input is greater than 6v Nominal: 50 ma max (not including the remote USB device load) Nominal: 0.25 watts
Cable Characteristics	Grade Color Diameter Bend Radius Connector Pull Strength	Plenum CMP (UL) Black 5 mm (0.2 inch) 8 mm (0.3 inch) minimum 10 Kg (22 lbs) maximum (never pull on the connector, use a pulling sock)
General	Connector Housing Dimensions	USB A Male (host side) 1.4 inch x 0.6 inch x 0.3 inch (35.6 mm x 15.3 mm x 7.6 mm) Total length including USB and strain relief: 2.3 inch (58.4 mm) USB A Female (device side) 1.8 inch x 0.6 inch x 0.3 inch (45.7 mm x 15.3 mm x 7.6 mm) Total length including strain relief: 2.2 inch (55.9 mm)
	Temp/humidity	Storage: -4 to +158°F (-20 to +70°C) / 5% to 90%, non-condensing Operating: +32 to +122°F (0 to +50°C) / 10% to 85%, non-condensing
	Regulatory	CE, RoHS
	EMI/EMC	CE, FCC Class A