



Western Enterprises

875 Bassett Road
Westlake, OH 44145-1142

Toll Free: 800.783.7890

Phone: 440.871.2160

Email: sales@westernenterprises.com

Website: www.westernenterprises.com

ITEM # CV-30R, OXYGEN GAS RIGHT HAND B-SIZE FEMALE NUT TO B-SIZE MALE REGULATOR ADAPTOR MODEL CHECK VALVE

Regulator Bushing Adaptor Model, B-Size (9/16"-18)

Easily mounts on outlet bushing of any regulator having a B-Size outlet. This model has the same flow capacity as the torch - type (1200 SCFH at 50 PSIG) when installed on a regulator. The Check Valve is to easy to see and is less subject to contamination, abuse and damage.

Oxygen RH, B-Size Female Nut to B-Size Male, to 125 PSIG (800kPa).



[Specifications](#) | [Check Valve Flow Specifications Charts](#) | [Additional Information](#) | [Prop 65](#) | [Note](#)

Specifications

Field	Industrial
Model	Regulator Bushing Adapter
Thread Size	9/16 in
Number of Threads per Inch	18
Maximum Working Pressure	125 psig
Gas Service	CGA-022
Gas	Oxygen
Valve Seat Material	Buna-N™

Check Valve Flow Specifications Charts

Check Valve Flow Specifications Charts

Flow curves presented here are based on air at 70 °F. To convert flows of other gases, multiply by the appropriate conversion factor listed on instruction sheets

included with all check valves.

Additional Information

Western's reverse flow Check Valves meet or exceed CGA and OSHA requirements (Pamphlet CGA-E2) and feature:

- Flows for cutting up to 12" of steel
- Machined high quality brass with stainless steel operating spring and valve disc
- Low open/close pressures: 1 - 1-1/2 PSIG open valve and 10 oz. reverse pressure to positively close valve
- 100% tested
- Made in U.S.A.

Additional Information

Prop 65

Warning

This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm.

Note

Note

Check Valves Do Not Stop Flashbacks.

UL Listed