



Western Enterprises

875 Bassett Road
Westlake, OH 44145-1142

Toll Free: 800.783.7890

Phone: 440.871.2160

Email: sales@westernenterprises.com

Website: www.westernenterprises.com

ITEM # CV-31L, FUEL GAS LEFT HAND B-SIZE FEMALE NUT TO B-SIZE MALE REGULATOR ADAPTOR MODEL CHECK VALVE

Regulator Bushing Adaptor Model, B-Size (9/16"-18)

Easily mounts on outlet bushing of any regulator having a B-Size outlet. This model has the same flow capacity as the torch - type (1200 SCFH at 50 PSIG) when installed on a regulator. The Check Valve is to easy to see and is less subject to contamination, abuse and damage.

Fuel Gas LH, B-Size F Nut to B-Size Male, to 50 PSIG (345 kPa).



[Specifications](#) | [Check Valve Flow Specifications Charts](#) | [Additional Information](#) | [Prop 65](#) | [Note](#)

Specifications

Field	Industrial
Model	Regulator Bushing Adapter
Thread Size	9/16 in
Number of Threads per Inch	18
Maximum Working Pressure	50 psig
Gas Service	CGA-023
Gas	Fuel Gases
Valve Seat Material	Buna-N™

Check Valve Flow Specifications Charts

Flow curves presented here are

Check Valve Flow Specifications Charts

based on air at 70 °F. To convert flows of other gases, multiply by the appropriate conversion factor listed on instruction sheets included with all check valves.

Additional Information**Additional Information**

Western's reverse flow Check Valves meet or exceed CGA and OSHA requirements (Pamphlet CGA-E2) and feature:

- Flows for cutting up to 12" of steel
- Machined high quality brass with stainless steel operating spring and valve disc
- Low open/close pressures: 1 - 1-1/2 PSIG open valve and 10 oz. reverse pressure to positively close valve
- 100% tested
- Made in U.S.A.

Prop 65**Warning**

This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm.

Note**Note**

Check Valves Do Not Stop Flashbacks.

UL Listed