



Western Enterprises

875 Bassett Road
Westlake, OH 44145-1142

Toll Free: 800.783.7890

Phone: 440.871.2160

Email: sales@westernenterprises.com

Website: www.westernenterprises.com

ITEM # CVM-4F, 1/4 INCH (IN) INLINE NATIONAL PIPE THREAD (NPT) MALE INLET TO FEMALE OUTLET BRASS HEAVY-DUTY CHECK VALVE

Inline NPT Check Valves, Heavy-Duty

- Heavy-Duty Check Valves are designed for high performance in demanding applications
- All styles feature low/open/close pressures: 3 oz. to open the valve and 10 oz. of reverse pressure for positive valve closing
- Check Valve seat material is durable Ethylene Propylene (EPDM)
- For use in high pressure pigtail assemblies

1/4" NPT Male Inlet to Female Outlet.



[Specifications](#) | [Check Valve Flow Specifications Charts](#) | [Additional Information](#) | [Prop 65](#) | [Note](#)

Specifications

Field	Industrial
Maximum Working Pressure	3000 psig
Material	Brass
Valve Seat Material	Ethylene Propylene (EPDM)

Check Valve Flow Specifications Charts

Check Valve Flow Specifications Charts

Flow curves presented here are based on air at 70 °F. To convert flows of other gases, multiply by the appropriate conversion factor listed on instruction sheets included with all check valves.

Additional Information

Western's reverse flow Check Valves meet or exceed CGA and OSHA requirements (Pamphlet CGA-E2) and feature:

Additional Information

- Flows for cutting up to 12" of steel
- Machined high quality brass with stainless steel operating spring and valve disc
- Low open/close pressures: 1 - 1-1/2 PSIG open valve and 10 oz. reverse pressure to positively close valve
- 100% tested
- Made in U.S.A.

Prop 65**Warning**

This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm.

Note**Note**

Check valves do not stop flashbacks.