



## Features

- The latest technology based on Crown's proprietary and patented DriveCore™ technology, these amplifiers are the next generation of PWM technology using cutting edge Class D amplifier topologies
- True Rack Density – power points of 300W, 600W, or 1250W in 4/8 channel configurations; includes bridgable outputs of 300-2500W, all in a 2U form factor, providing flexibility in designs
- Minimum Guaranteed Power Ratings – DCi amplifiers are guaranteed to deliver at least the rated power in the specifications over a longer period of time than any other competing amplifier
- Direct Drive "Constant Voltage" capabilities on a channel by channel basis for 70Vrms or 100Vrms amplification without the use of a step up frequency limiting transformer for higher audio quality

- HiQnet Audio Architect™ supported amplifier
- Advanced PFC universal power supply provides market-leading efficiency, and is designed to deliver maximum power no matter where the amplifier is located; Universal AC input accepts 100 – 240VAC, 50/60Hz (±10%)
- DriveCore includes five patents that are also included in Crown's flagship touring amplifier I-Tech HD4, providing best-in-class versatility and durability
- TCP/IP based protocol in HiQnet™ for network monitoring and control
- Revolutionary cooling system focuses airflow on parts that need it most, maximizing efficiency while minimizing heat and noise
- Integrated Dante™ / AES67 networked audio – simplifies installation by enabling Dante / AES67 networked audio signals to be sent directly to the amplifier.

### Network Monitoring and Control features include:

- Continuous Load Monitoring
- Comprehensive Error Reporting
- Pilot Tone Monitoring
- Programmable General Purpose Input/Output (GPIO) Ports

### Digital Signal Processing (DSP) features include:

- LevelMAX™ Limiters for Inputs and Outputs with Thermal Limiting
- Input Compressor
- Input and Output Delay
- Input and Output EQ
- Signal Generator
- Crossover

INSTALLS ANYWHERE. OUTPERFORMS EVERYTHING.

# DriveCore™ Install DA Series



4|300DA, 4|600DA models shown



8|300DA model shown



4|1250DA model shown

Performance Specifications	4 300DA	4 600DA	8 300DA	8 600DA	4 1250DA
Frequency Response (8Ω, 20Hz - 20kHz)				±0.25dB	
Dante Input Signal to Noise Ratio (ref. rated power, 8ohm, 20Hz-20kHz)				>108dB	
Total Harmonic Distortion (at full rated power, 20Hz - 20kHz)				0.35%	
Voltage Gain (at Maximum Level Setting)				34dB	
Damping Factor (20Hz to 100Hz)	>1000	>1000	>1000	>1000	>1500
Input Impedance (nominal balanced, unbalanced)				10kΩ, 5kΩ	
Maximum Input Level before Compression (Low Gain Mode)				+20dBu	
Load Impedance Stereo/Dual Mode				2Ω - 16Ω; 70Vrms and 100Vrms	
Load Impedance Bridge Mono				4Ω - 16Ω; 140Vrms and 200Vrms	
Cooling	Continuously variable speed forced air, front to back airflow				
Maximum Fan Noise (re dBA SPL @ 1M)	45	45	47	47	47
Required AC Mains (±10%)	100Vrms - 240Vrms ~50/60Hz				
Power Connector	15A IEC	15A IEC	15A IEC	20A IEC	20A IEC

## Power Matrix

Model	Channels	2Ω	4Ω	8Ω	70Vrms	100Vrms
4 300DA	4	150W	300W	300W	300W	300W
4 600DA	4	300W	600W	600W	600W	600W
8 300DA	8	150W	300W	300W	300W	300W
8 600DA	8	300W	600W	600W	600W	600W
4 1250DA	4	1250W	1250W	1250W	1250W	1250W

## Physical Specifications

Width	19 in. (48.3 cm)				
Height	3.5 in. (8.9 cm)				
Depth	14.25 in. (35.63 cm)	14.25 in. (35.63 cm)	14.25 in. (35.63 cm)	17 in. (42.5 cm)	17 in. (42.5 cm)
Weight	20.1 lbs (9.12 kg)	20.1 lbs (9.12 kg)	23.5 lbs (10.66 kg)	30 lbs (13.60 kg)	30 lbs (13.60 kg)