

LED2000 PLUS SERIES



The PLUS Series Panels from Dracast are versatile lighting instruments designed for use in the studio or on location. The build and features of the PLUS Series represent the feedback from lighting professionals worldwide who have helped to make our best even better.

PLUS Series Panels are available in three sizes: the LED500, LED1000, and LED2000. The LED2000 is a high-output, 24" x 15" rectangular panel light that makes it ideal for studios and other demanding applications. The LED1000 is a more familiar, traditional version, and the LED500 is built for portability and other settings where its compact size is a must.

Much like the Pro Series from Dracast, the PLUS Series is available in three color temperature models: 3200K (Tungsten), 5600K (Daylight), and 3200K - 5600K (Variable CCT). All three versions deliver continuous 0 - 100% dimming and excellent color rendition across the color spectrum. Additionally, PLUS Series lights can be battery powered for field work but also now include Cat 5 DMX In / Out for remote control applications.

PLUS Series lights incorporate a beautiful new digital display that delivers a readout of the CCT, light output, and DMX address. PLUS Series light are also still some of the most durable LED lights available, being built entirely on an anodized aluminum frame and chassis.

Photometric Data	3 ft / 0.9 m	6 ft / 1.8 m	9 ft / 2.7 m	12 ft / 3.6 m
LED2000 PLUS 5600K DRL2000PD	929 fc 10000 lux	321 fc 3450 lux	166 fc 1785 lux	98 fc 1050 lux
LED2000 PLUS 3200K DRL2000PT	794 fc 8550 lux	274 fc 2950 lux	137 fc 1475 lux	84 fc 900 lux
LED2000 PLUS 3200K - 5600K DRL2000PB	376 fc @ 3200K	127 fc @ 3200K	65 fc @ 3200K	39 fc @ 3200K
	753 fc @ 4400K	251 fc @ 4400K	123 fc @ 4400K	73 fc @ 4400K
	390 fc @ 5600K	139 fc @ 5600K	68 fc @ 5600K	40 fc @ 5600K
	4050 lux @ 3200K	1370 lux @ 3200K	700 lux @ 3200K	420 lux @ 3200K
	8100 lux @ 4400K	2700 lux @ 4400K	1325 lux @ 4400K	785 lux @ 4400K
	4200 lux @ 5600K	1500 lux @ 5600K	730 lux @ 5600K	430 lux @ 5600K

Part No.	Included
DRL2000PD	LED2000 PLUS Series 5600K Daylight, Aluminum 5/8" Baby Pin Yoke, 24V A/C Power Supply, User Manual
DRL2000PT	LED2000 PLUS Series 3200K Tungsten, Aluminum 5/8" Baby Pin Yoke, 24V A/C Power Supply, User Manual
DRL2000PB	LED2000 PLUS Series 3200K - 5600K Variable Color Temp, Aluminum 5/8" Baby Pin Yoke, 24V A/C Power Supply, User Manual



Specifications Details

Optical System	2048, 5mm LED bulbs in 32 x 64 arrangement.
Light Aperture	13 x 22 inches (330 mm x 558)
Beam Angle	45 degrees
Weight	9.5 lbs
Handling	Aluminum Yoke, Dual Locking Tilt Control
Mounting	Baby 5/8" Pin
Tilt Angle	+/- 90 degrees
Voltage Input	24 V DC
Power Consumption	130 W
Power Connection	4-Pin XLR, 110 - 240 VAC, 50 - 60 Hz, 2.0 A
Battery Connection	N/A
Battery DC Voltage	N/A
Battery Light Output	N/A
Color Temperature	3200K - 5600K (Variable or fixed color temperature depending on model)
Color Rendition	CRI > 95
Dimming	0 - 100% Continuous
Controls	Local On-Board Manual Controls, 5-Pin DMX In / Out Ports
Housing Color	Anodized Blue / Black
Housing Build	Aluminum
Est. LED Lifetime	50,000 hours

Available Accessories

DRBD2000	4-Way Adjustable Barndoors
DRFTRP2000	Dracast Diffusion and CTO Semi-Rigid Filter Packs
DRDLS805	Dracast Portable Light Stand
DB0072 - 8505F	Injection Molded Hard Plastic Travel Case