



CEC DOE FC

PERFORMANCE FEATURES

- Aluminum housing with high grade acrylic panel.
- Innovative, easy installation in minutes.
- Aluminum mounting plate allows top, back or end mount.
- Removable directional indicators.
- 120V/277VAC Dual voltage operation
- Letter 6" height with 3/4" stroke. Super bright RED or GREEN LED lamps.
- White mylar
- Built-in 3.6V600mAh Nickel cadmium battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.
- Five years warranty for the electrical parts and housing.

ORDERING INFORMATION

Model Section	EDGE-ES-01		
FAMILY	FACEPLATE	LENS	PANEL
EDGE-ES-01	1(Single)	R(REDF) G(GREEN)	C(CLEAR)

ELECTRICAL INFORMATION

Model	Rated Voltage	Input Current	Input Watt	LED Type	Charging Time	EMERGENCY RUN TIME
EDGE-ES-01	120/277V	0.027-0.013A	3.5W	12Pcs Red LEDs	24 Hrs	180 Mins
EDGE-ES-02	120/277V	0.027-0.013A	3.5W	12Pcs Green LEDs	24 Hrs	180 Mins

PACKING INFORMATION

SKU #	Standard Pack	Dimension	Master Pack	Dimension
EDGE-ES-01	1 Pack	12.70X10.75X1.65 in	6 Pack	15.16X14.37X12.99 in

PRODUCT DIMENSIONS

