



SWITCHABLE RED/GREEN LED's



CEC DOE FC

PERFORMANCE FEATURES

- Injection-mold thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Letters 6" height with 3/4" stroke. Optional RED or GREEN letters.
- SALIDA faceplate available.
- Single or double face (Universal)
- Universal J-box mounting pattern.
- 120V-277VAC Universal voltage operation.
- 2X1W SMT LED lamp heads for emergency mode.
- Built-in 3.6V1000mAh Ni-MH battery for minimum 90 minute emergency operation.
- Built-in 3.6V2000mAh Ni-MH battery for minimum 90 operation. ESC-C-S-02
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.
- Five years warranty for the electrical parts and housing.

ORDERING INFORMATION

Model Section	ESC-C-S-01/ESC-C-S-02		
FAMILY	LENS	HOUSING COLOR	REMOTE CAPACITY
ESC-C-S-01	S - Switchable color	W-White	Blank (Without) RC (With Remote)
ESC-C-S-02			

ELECTRICAL INFORMATION

Model	Rated Voltage	Input Current	Input Watt	LED Type	Charging Time	EMERGENCY RUN TIME
ESC-C-S-01	120/277V	0.032-0.017A	2W	6 LEDs for red version / 6 LEDs for green version +2 lamp heads	24 Hrs	90 Mins
ESC-C-S-02	120/277V	0.047-0.028A	2.8W	6 LEDs for red version/6 LEDs for green version 2 lamp heads 2W remote loads	24 Hrs	90 Mins

PACKING INFORMATION

SKU #	Standard Pack	Dimension	Master Pack	Dimension
ESC-C-S-01	1 Pack	16.46X7.24X2.05 in	6 Pack	17.52X12.2X8.27 in
ESC-C-S-02	1 Pack	16.46X7.24X2.05 in	6 Pack	17.52X12.2X8.27 in

PRODUCT DIMENSIONS

