



CEC DOE FC



PERFORMANCE FEATURES

- Injection-molded thermoplastic ABS housing and polycarbonate cover, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Letters 6" height with 3/4" stroke. Optional RED or GREEN letters.
- Universal J-box mounting pattern
- 120V/277VAC Dual voltage operation
- Single or double face(Universal).
- Built-in 3.6V1200mAh Ni-Mh battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.
- Five years warranty for the electrical parts and housing.

ORDERING INFORMATION

Model Section	ESC-S-W		
FAMILY	TYPE	LENS	HOUSING COLOR
ESC-S-W	EE1(SIGN ONLY) EC(WITH TWO HEAD LAMPS)	R(RED)	W(WHITE)

ELECTRICAL INFORMATION

Model	Rated Voltage	Input Current	Input Watt	LED Type	Charging Time	EMERGENCY RUN TIME
ESC-S-W	120/277V	0.026-0.015A	2.9W	10pcs RED LEDs	24 Hrs	90 Mins

PACKING INFORMATION

SKU #	Standard Pack	Dimension	Master Pack	Dimension
ESC-S-W	1 Pack	12.60X13.33X2.56 in	6 Pack	14.57X13.78X16.73 in

PRODUCT DIMENSIONS

