

**Combi Style Aluminum Bead Breaker - 10 Tons of Force, 2.75" Stroke**

Model #40801




MODEL 40801



- ▶ **Aluminum Construction - Lightweight**
- ▶ 10 Tons of Bead Breaking Force
- ▶ Comparable to the #10101, Combi Bead Breaker
- ▶ To be used on 3-Piece Wheel Assemblies.
- ▶ Extended Jaw for Deep Dish Style Wheels (Extended Flange)
- ▶ Stroke: 2.75" | 70mm
- ▶ Weight: 19 lbs. | 8.5 kg

**SPECIFICATIONS**



**MODEL 10247**

- 40801 - "Combi" Bead Breaker Tool**  
**10592 - Pump, Air Hydraulic, 5 Quart**  
**10604 - Hose assembly with Hose Coupler, 8'**  
**10601K - Air Reducer, 6" Whip-Hose**

**MODEL 10246**

- 40801 - "Combi" Bead Breaker Tool**  
**10590 - Pump, Air Hydraulic, 2 1/2 Quart**  
**10604 - Hose Assembly with Hose Coupler, 8'**  
**10601K - Air Reducer, 6" Whip-Hose**

**MODEL 10245**

- 40801 - "Combi" Bead Breaker Tool**  
**10500 - Turbo II Pump, Air Hydraulic, 3 1/2 Quart +**  
**10604 - Hose Assembly with Hose Coupler, 8'**  
**10601K - Air Reducer, 6" Whip-Hose**



MODEL 10247



MODEL 10246



MODEL 10245


**Aluminum Bead Breaker - 20 Tons of Force, For 5 Piece Wheels**

Model #40802



MODEL 40802

- ▶ **Aluminum Construction - Lightweight**
- ▶ **Specialty Designed Claws -** Able to be used on Wheels with Smaller Bead Pockets. (see chart below)
- ▶ **Includes:** (2) Aluminum Style Wedges **40208-20** to increase usage on wider range of wheel assemblies & **40802-6A** Claw to be used on 5 Piece Wheel Assemblies 25" - 51"
- ▶ Bead Breaker with Swivel Style Coupler Available: Model #40802S
- ▶ Stroke: 2.75" | 70mm
- ▶ 20 Tons of Bead Breaking Force
- ▶ Weight: 17.6 lbs. | 8 kg



| Part #   | A          | B         | C          | D         |
|----------|------------|-----------|------------|-----------|
| 40802-6A | 1.18" 30mm | 0.31" 8mm | 3" 78mm    | 1.7" 43mm |
| 40802-6B | 1.14" 29mm | 0.4" 10mm | 3" 78mm    | 1.7" 43mm |
| 40802-6C | 1.42" 36mm | 0.4" 10mm | 4" 100mm   | 2" 50mm   |
| 40802-6D | 1.18" 30mm | 0.35" 9mm | 3.35" 85mm | 1.5" 37mm |

