

Flange Rim Puller

Model #90300



MODEL 90300



- ▶ Designed to lift the rim base from the tire, remove the bead seat band from the tire, or aid in the seating of the bead seat band during inflation.
- ▶ Features 4-point chain hook assembly.
- ▶ Easily attaches to the boom.
- ▶ 21,600 lbs. capacity.
- ▶ 5,400 lbs. capacity per chain.
- ▶ Weight: 34 lbs. | 15 kg

Bead Hooks



MODEL 90400



MODEL 90401



MODEL 90402

- ▶ Fits all truck mounted tire cranes.
- ▶ Heavy duty, rugged construction.
- ▶ Contour of hook same as tire bead.
- ▶ Angle of tool won't allow tire to slip off when lifting.
- ▶ Prevents bead damage.

Model #	Rated For	Capacity	Weight	Height	Width
90400	Light Duty	5,500 lbs.	33 lbs. 15 kg	17.5" 445mm	8.25" 210mm
90402	Medium Duty	12,000 lbs.	39 lbs. 18 kg	19" 483mm	11" 280mm
90401	Heavy Duty	16,000 lbs.	59 lbs. 27 kg	24" 610mm	14.5" 368mm

OTR Large Tire O-Ring Installer - Lightweight Aluminum Construction

Model #40807

NEW!



MODEL 40807

- ▶ Used on 25" to 36" OTR Tires
- ▶ Designed and built to manually install and remove O-Rings
- ▶ Unit is also used to separate the inside and outside beads
- ▶ Assists in the removal and installation of the lock ring



Tire Diameter	Width	Length	Height	Weight
25"-36" 635-914mm	3" 76mm	32.5" 825mm	14.5" 368mm	36 lbs. 16 kg