

Technical Datasheet SLM1650XD1S0-GO REV. A



DuraBrite Explorer X16 is the most powerful and longest running portable light in its class. At only 20lbs, it can run for 7 hours at full blast on a single charge, delivering 16,670 blasting lumens. The integrated on-body precision dimmer allows it to be dimmed down for extended run time.

Based on DuraBrite's bestselling model, the Mini, *Explorer X16* is designed for users who require an extensive amount of light for commercial, industrial, or safety operations. The integrated battery has an impressive 770Wh capacity packed into a very compact unit.

The *X16* comes with a built-in battery indicator. A toggle is also available that allows the user to switch between dimming mode and instant full blast with the flick of a switch.

The Explorer X16 is IP65 rated, allowing usage in harsh outdoor environments.

The base is equipped with shock absorbing non-slip rubber feet so the light can be placed on a wide variety of surfaces. An optional flood lens is available to change optics from spot to flood in seconds.

The X16's tremendous capability will continuously power you through your mission and activities with no down time and you will no longer fear the dark. It has won the USAF Innovative Technology award and is the light of choice by USAF, fire departments, and other agencies that demand high performance, portable lighting.

DuraBrite Explorer X16 – Light up the Night with Confidence!



Advanced Battery Technology



Extreme Weather Resistance



Designed & Assembled In USA



Technical Datasheet SLM1650XD1S0-GO REV. A

Optical & Electrical Characteristics (All ratings are at 25°C unless otherwise specified)

LED Color, CCT Typical = 5000K (Neutral white)

Lower limit = 4700K; Upper limit = 5300K

Brightness 16,670 lm (raw)

Beam Angle 20 deg (Spot) 80 deg (Flood)

Charger Input Voltage Auto detect voltages

100 – 240VAC 50-60Hz Single Phase

Charger Output Voltage /
Battery Input Voltage 16.3VDC

Charger Status Indicator Green – Charge complete

Red – Charging

Charging Temperature 32°F to 100°F (Storage Temperature) (-4°F to 176°F)

Battery Capacity 770Wh max

Run Time Approx. 7 hr continuous max output#

Run time varies based on ambient temperature

and battery age

Battery Status Indicator Actual voltage shown. Refer to Label

Charging Time 6 hrs for a full charge

Battery Certification UN38.3 Certified for:

Altitude

• Thermal

Vibration

Shock

• External Short Circuit

• Impact / Crush

Overcharge

Forced discharge



Technical Datasheet SLM1650XD1S0-GO REV. A

Mechanical Characteristics

Water Resistance IP65

(protected against waterjet from any angle, do not

submerge)

Temperature Range -4°F to 120°F

Overall Weight 19.9 lb

Warranty Terms

We stand behind our products. This product is covered by DuraBrite's 5 Year Limited Warranty against material and manufacturing defects. It does not cover application and conditions that are outside of the product design parameters, abuse, and normal wear-and-tear.