



Ethernet switch managed gigabit ICRL-M-8RJ45/4SFP-G-DIN

- 8 Gigabit Ethernet RJ45 ports and 4 Gigabit SFP ports with DDM function
- Layer 2 Network Performance
- Redundant power input with an input power range of 10 to 36VDC
- IP20 with an extreme operating temperature range of -40 to 75°C
- Suitable for PROFINET IO and EtherNet/IP


Ethernet managed gigabit switch with 8 RJ45 and 4 SFP ports



Function

The ICRL-M-8RJ45/4SFP-G-DIN is a Gigabit industrial Ethernet Switch with eight RJ45 ports and four Gigabit SFP sockets for optical fiber network connection. It provides an Ethernet MAC controller with 24 Gbps Switch fabric bandwidth with 9K jumbo frame forwarding. The robust system design makes the switch survive under harsh outdoor environment with extreme electric magnetic interference and the variation of environment temperature. The switch also provides your network infrastructure with great performance and safety with network access control, and the ability to handle burst packets with smart buffer management for IP surveillance in real infrastructures.

Dimensions



Technical Data

General specifications

UL File Number E185778

Functional safety related parameters

MTBF 69 years


Technical Data

Ethernet Interface	
Connection type	RJ45 , SFP
Auto-MDI(-X)	yes
Autonegotiation	yes
Ethernet Interface	Industrial Ethernet
Transfer rate	8 - 10BASE-T, 100BASE-TX, 1000BASE-T, 4 - SFP 100/1000 Mbps
Management	IPv4, IPv6, Console, HTTP, HTTPS, PortVision DX, SFTP, SNMP (v1, v2c, and v3), SSH, Telnet, TFTP
MIB	MIB-II, Bridge MIB, Ethernet-like-MIB, VLAN MIB, IGMP MIB, Private MIB
Monitoring	LLDP, Port Mirroring, RMON
Multicast	IGMP Query, IGMP Snooping, GMRP
Network performance	CFM, Jumbo Frames, QoS, CoSQueue Mapping, DSCP Priority Mapping
Network redundancy	STP, RSTP, MSTP, ERPS, Redundant Ring, LACP, Static Port Aggregation
Network services	DHCP Server (with Option 82), NTP, IEEE 1588 PTPv2 over UDP/IP
Notifications	E-Mail, Fault Relay, SNMP Traps, Syslog
Safety	RADIUS, TACACS+, DHCP Snooping, IP Source Guard, Dynamic ARP Inspection, MAC-Based Port Security
Traffic filtering	Storm Control (Broadcast, Multicast, and DLF), Rate Control, VLAN, Private VLAN, QinQ Tunneling, GVRP, IP Filtering, MAC Filtering, ARP Filtering
Cable type	Category 5e or better
Switch properties	
Hardware watchdog timer	10 s reset timer
MAC address table size	16K
Operating mode	Store and forward
Packet buffer size	1.5M Bytes shared memory for packet buffer with intelligent memory management unit for burst data traffic
Priority queues	8
VLAN entries	IEEE 802.1Q Tag VLAN with 256 VLAN Entries and provides 2K GVRP entries; 3 VLAN link modes- Trunk mode, Hybrid mode and Link access mode
SFP support	100BASE-FX Fiber, 1000BASE-SX/LX/LHX/XD/ZX
Standards	
IEEE 802.3 10BASE-T	yes
IEEE 802.3u 100BASE-TX	yes
IEEE 802.3x Flow Control and Back-pressure	yes
IEEE 802.1p Class of Service (CoS)	yes
IEEE 802.3ab 1000BASE-T	yes
IEEE 802.1AB Link Layer Discovery Protocol (LLDP)	yes
IEEE 802.1Q VLAN and GVRP	yes
IEEE 802.1D-2004 Rapid Spanning Tree Protocol (RSTP)	yes
IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)	yes
IEEE 802.3ad Link Aggregation Protocol (LACP)	yes
IEEE802.1ad QinQ Tunneling	yes
IEEE 802.1x Port Based Network Access Protocol	yes
ITU-T G.8032 ERPS	yes
Indicators/operating means	
LED indication	see manual
Electrical specifications	
Rated operating voltage	U_e 10 ... 36 V DC
General information	Redundant power, digital output (relay output) rating 0.5A Max. @ 24V DC, Digital input
Nominal voltage	24 V DC

Technical Data

Inputs/Outputs	
Number/Type	8 x RJ45 , 4 x SFP
Directive conformity	
Electromagnetic compatibility	
Directive 2014/30/EU	EN 61000-6-2, IEC 61000-6-2 , EN 61000-6-4, IEC 61000-6-4
Standard conformity	
Electrical safety	CSA C22.2 No. 60950 / CSA C22.2 No. 60950/UL60950
Emitted interference	CISPR 22 , FCC Part 15 Subpart B Class A , EN61000-6-4, IEC61000-6-4
Noise immunity	EN61000-6-2, IEC61000-6-2
Ambient conditions	
Ambient temperature	-40 ... 75 °C (-40 ... 167 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F)
Relative humidity	max. 95 %
Altitude	0 ... 3048 m
Mechanical specifications	
Housing length	127 mm
Housing width	84 mm
Housing height	160 mm
Degree of protection	IP30
Connection	Power Supply Terminal Block (4-pin) Ethernet 8 x RJ45 , 4 x SFP
Material	
Housing	aluminium, black
Mass	1460 g
Construction type	Cabinet module
Mounting	DIN rail or direct panel mounting

Wiring Diagram




Console port			
1	n.c.	5	GND
2	n.c.	6	RxD
3	TxD	7	n.c.
4	n.c.	8	n.c.















	1000BASE-T	100BASE-TX
1	BI_DA+	Tx+
2	BI_DA-	Tx-
3	BI_DB+	Rx+
4	BI_DC+	
5	BI_DC-	
6	BI_DB-	Rx-
7	BI_DD+	
8	BI_DD-	

Release date: 2021-04-14 Date of issue: 2021-04-14 Filename: 70114058_eng.pdf

Indication






















Accessories

	V45-G-C5-GN1M-PUR-E1S	Ethernet bus cable male cordset single-ended RJ45, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	V45-G-C5-GN3M-PUR-E1S	Ethernet bus cable male cordset single-ended RJ45, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	V45-G-C5-GN10M-PUR-E1S	Ethernet bus cable male cordset single-ended RJ45, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	V45-G-C5-GN1M-PUR-E1S-V45-G	Ethernet bus cable RJ45 to RJ45 PROFINET-coded, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	V45-G-C5-GN3M-PUR-E1S-V45-G	Ethernet bus cable RJ45 to RJ45 PROFINET-coded, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	V45-G-C5-GN10M-PUR-E1S-V45-G	Ethernet bus cable RJ45 to RJ45 PROFINET-coded, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	V45-G-C5-GN20M-PUR-E1S-V45-G	Ethernet bus cable RJ45 to RJ45 PROFINET-coded, 4-pin, PUR cable green, Cat5e, shielded, UL approved, drag chain suitable
	SFP-M-2KM-F-N	Multi-mode 2KM 100BASE-FX Fast Ethernet Fiber SFP
	SFP-M-2KM-F-W	Multi-mode 2KM 100BASE-FX Fast Ethernet Fiber SFP
	SFP-M-2KM-G-W	Multi-mode 2KM 100BASE-LX Gigabit Ethernet Fiber SFP
	SFP-M-550M-G-N	Multi-mode 550m 1000BASE-SX Gigabit Ethernet Fiber SFP
	SFP-M-550M-G-W	Multi-mode 550m 1000BASE-SX Gigabit Ethernet Fiber SFP
	SFP-S-100KM-F-W	Single-mode 100KM 100BASE-ZX Fast Ethernet Fiber SFP
	SFP-S-10KM-G-N	Single-mode 10KM 1000BASE-LX Gigabit Ethernet Fiber SFP

Release date: 2021-04-14 Date of issue: 2021-04-14 Filename: 70114058_eng.pdf

Accessories

	SFP-S-10KM-G-W	Single-mode 10KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-10KM-G-W-BIDI-A	Single-mode BiDi-A 10KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-10KM-G-W-BIDI-B	Single-mode BiDi-B 10KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-110KM-G-W	Single-mode 110KM 1000BASE-UZX Gigabit Ethernet Fiber SFP
	SFP-S-120KM-F-W	Single-mode 120KM 100BASE-FX Fast Ethernet Fiber SFP
	SFP-S-20KM-F-W	Single-mode 20KM 100BASE-FX Fast Ethernet Fiber SFP
	SFP-S-20KM-F-W-BIDI-A	Single-mode BiDi-A 20KM 100BASE-BX Fast Ethernet Fiber SFP
	SFP-S-20KM-F-W-BIDI-B	Single-mode BiDi-B 20KM 100BASE-BX Fast Ethernet Fiber SFP
	SFP-S-20KM-G-W	Single-mode 20KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-20KM-G-W-BIDI-A	Single-mode BiDi-A 20KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-20KM-G-W-BIDI-B	Single-mode BiDi-B 20KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-30KM-F-N	Single-mode 30KM 100BASE-LX Fast Ethernet Fiber SFP
	SFP-S-30KM-F-W	Single-mode 30KM 100BASE-LX Fast Ethernet Fiber SFP
	SFP-S-30KM-G-W	Single-mode 30KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-40KM-G-W	Single-mode 40KM 1000BASE-EX Gigabit Ethernet Fiber SFP
	SFP-S-50KM-G-W	Single-mode 50KM 1000BASE-XD Gigabit Ethernet Fiber SFP
	SFP-S-60KM-F-W	Single-mode 60KM 100BASE-ZX Fast Ethernet Fiber SFP
	SFP-S-70KM-G-W	Single-mode 70KM 1000BASE-LX Gigabit Ethernet Fiber SFP
	SFP-S-90KM-G-W	Single-mode 90KM 1000BASE-ZX Gigabit Ethernet Fiber SFP