



1000VA 600W 6 Outlets UPS

IV-CP1000

Features:

- . 1000VA 600W 6 outlets UPS
- . Battery run time 60~70 minutes
- . LED indicator
- . 5.1" x 15" x7.6"



Specification	IV-CP1000
Interface	USB
AC Input Capacity on Battery	1000VA
AC Input Frequency	50 or 60 Hz+/-5% (auto sensing)
AC Input Voltage	100V or 110V/115V/120V or 220V/230V/240V +/- 25% at line input
AC Output Frequency	50 or 60 Hz +/- 0.5%
AC Output Transfer	2/4 milliseconds, including detection time
AC Output Voltage	Simulated sine wave at 100V or 110V/115V/120V or 220V/230V/240V +/- 25%
AC Output Voltage Regulation	AVR automatically increase output voltage 15% above input voltage if -9% to -25% of nominal.
	AVR decrease output voltage 13% below input voltage if +9% to +25% of nominal
Alarm Battery Backup	Slow beeping sound (about 0.47 Hz)
Alarm Battery Low	Rapid beeping sound (about 1.82Hz)
Alarm Overload	Continue beeping sound
Battery Protection	Auto discharge protection
Battery Run Time	60 - 70 minutes
Battery Type	UPS output cut off immediately or input fuse protection
Battery Typical	6 hours (to 90% of full capacity)
Environment Ambient	3,500 meters max. elevation, 0-95% humidity non-condensing, 0-40 deg c
Environment Audible	<40dBA (1 meter from surface)
Environment Storage Condition	15,000 meters max. elevation
Indicator	LED
Protection Inside Protection	UPS output cut off immediately or input fuse protection
Protection Overload	UPS automatic shutdown if overload exceeds 110% nominal at 60 sec and 130% at 3 sec
Protection Spike	480 Joules / 2ms
Protection Unit	Fuse for overload & short circuit protection
Dimensions	5.1" x 15" x 7.6"
Weight	29.5 Lbs / 13.4 Kg
Warranty	1-Year Limited Warranty