



# 4CH H.264 PoE Network Video Recorder

## IV-MX4PoENVR

- Support up to 2MP IP Camera
- 6 ports (4 cameras, one internet, one LAN)
- HDMI and VGA output
- Standalone Linux embedded system
- Web-based management
- Support up to 4 PoE network cameras
- Support P2P remote access
- Support iCMS system
- Auto system management
- Support motion detection & alert
- Support touch monitor
- QR code quick access



**ONVIF** Free App for iOS / Android



### P2P connection solution



With easy QR code settings, you can monitor with smart phones and tablets over the internet from anywhere, anytime.



Specification		IV-MX4PoENVR	
<b>Camera Input</b>		4CH	
<b>Video</b>	Input	4CH * 2MP (PoE)	
	Output	Max. 1920x1080 1 HDMI with Audio and 1 VGA	
<b>Audio</b>	Input	1	
	Output	1	
<b>Display</b>	Split Screen	1,4, PIP	
	Auto Channel Switching	Switching time : 1 - 99 sec	
	Mode	Zoom ( Digital x2- x5 ), PIP, Auto SEQ.	
<b>Recording</b>	Recording Throughput (60Hz IP Camera)	1920 x 1080, 1280 x 720, 704 x 480 (30 fps)	
	Mode	Continuous, Event, Schedule	
<b>Playback</b>	Search Mode	Date/Time, Event	
	Zoom	*Digital ( x2 - x5 )	
<b>Network</b>	Network Interface	10/100 Ethernet	
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS, FTP, SMTP	
	ONVIF	YES	
	Remote Software	iWatch DVR, IE Browser, iCMS	
	Account	1 Admin + 10 Users	
<b>Backup</b>	Mobile Device System	Windows Phone, iPhone, iPad, Android	
	Interface	USB 2.0	
	Audio Backup	YES	
<b>Alarm OSD &amp; DVR Control</b>	Backup Type	Network, Ext. USB flash device etc	
	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)	
	Multi-Language	Supported	
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)	
<b>System</b>	System Upgrade	USB Flash Drive, iWatch DVR	
	Operating System	Embedded Linux OS	
	SATA Devices	Max. 1 x SATA Devices (HDD x 1)	
	External HDD	No	
	Sensor In (NO, NC) Relay Out		Sensor-in x 4
			Relay-out x 1
	Serial Interface	RS-485	
	USB 2.0 Ports	USB2.0 x 2	
	Dimension	11.02" x 2" x 7.99"	
	Weight (w/o HDD)	2.27 lbs (1.03KG)	
Power Rating		DC 48V 1.25A 60W	
		Adapter 110/220V	