



Public View Monitors

IV-PVM19DIS

Features:

- . PIXIM Wide Dynamic 690 HTVL-E Camera Built-in
- . LED backlight, 40% power saving
- . 3D Noise reduction & Comb filter
- . Camera Loop out (BNC)
- . SD-Card reader, HDMI, Composite video support
- . Auto Switch between different channel on/off
- . On screen Warning Message on/off
- . Super Slim Metal housing design
- . Full glass cover front face
- . Movement Sense wake up
- . 2-Axis adjustment, Easy Access to Camera
- . Full function remote control
- . Safety working voltage
- . Cooling fans build in



Specification		IV-PVM19DIS
Display	Screen Size	19 inch
	Aspect Ratio	4:3
	Backlight	LED
	Viewing Angle	170°/170°
	Resolution	1280 x 1024
	Response Time	5ms
	Contrast Ratio	1000:1
	Brightness	300 cd/m ²
Input	VGA	1
	CVBS (BNC)	1
	HDMI	1
	S-Video	1
	Audio (R/L)	1
Output	Camera (BNC)	1
	CVBS (BNC)	1
Power	Consumption	< 25W
	Voltage	AC 100-240V 50-60Hz
System	PAL / NTSC Auto Detection & OSD Control	
WDR Camera		
Sensor	Sensor	1/3 " DPS Sensor
	Video Format	PAL / NTSC
	Resolution	690 HTVL-E
	Mini illumination	0.1Lux
	S/N Ratio	≥ 50 db (AGC OFF)
Control	WDR Control	Medium, Normal, Low, High
	BLC	ON,OFF
	AGC	Normal, Low, High
	White Balance	Tracking White Balance, Auto White Balance(ATW) (Auto White Balance) 2200-10000 K
	D/N	OFF, External Control, Auto; ON
	SYNC Mode	Internal
Power	Voltage	DC 12V
	Current	<150 mA
Lens	2.8 - 12 mm	
Size	56(φ)*57(H)	
Weight	3.5274 oz / 100g	
Temperature	14 °F ~ 122 °F / -10°C ~ 50 °C	