

# Crystal Quest® Luxury Shower Power INSTALLATION AND OPERATION GUIDE



# ONLINE WARRANTY INFORMATION CrystalQuest.com/warranty.html

Copyright 2020 Crystal Quest® All rights reserved MADE IN THE USA








## INSTALLATION INSTRUCTIONS

- 1. Remove existing shower head from shower arm (pipe) by unscrewing it counterclockwise (do not unscrew shower arm).
- Install shower head by turning clockwise onto other side of diverter valve.\*
- 4. If leaks appear, tighten or reinstall.



\*DO NOT OVER TIGHTEN OR CROSS THREAD

\*Thread seal tape may be required.

**OPERATING SPECIFICATIONS:** 

Pressure Range: 30-60 psi (2.1-4.1 bar)
Temperate Range: 40-110°F (4.4-43.3°C)

Optimum Service Flow: 2-4 gpm

# BEFORE ENTERING THE SHOWER

a new cartridge ar

equire


2. Cool to the desired temperature before entering shower.



## WHEN AND HOW TO CHANGE YOUR CARTRIDGE

#### CARTRIDGE REPLACEMENT

- 1. Unscr om the shower arm. It may not be necessary to unscrew the complete assembly from the shower arm (Fig 1).
- 2. Remove the old cartridge and replace with a new cartridge.
- Make sure both O-rings are properly seated in the O-ring grooves. Apply a small amount of lubricant, such as any non-petroleum oil (do not use coconut oil), to each O-ring (Fig 2).
- 4. Screw the housing back together (Fig 3).



#### MAINTENANCE / CAUTION

Caution: Protect disc from freezing temperatures. If freezing temperatures exist, drain unit and set wet replacement disk aside to dry. Protect disk from direct sunlight. Not intended for outdoor use.

- Do not use non-Crystal Quest® replacement cartridges.
- Do not use non-Crystal Quest® parts or modify/tamper with unit.

Note: O-rings may need to be cleaned and lubricated periodically with any non-petroleum oil (do not use coconut oil).

#### PROBLEMS / SOLUTIONS

- 1. Leaking around threaded connections: Apply thread seal tape to threads
- 2. Leaking between two housing halves: Check that O-rings are properly seated in grooves and that housing halves are snuggly threaded together

#### **BACK FLUSHING**

- 1. Unscr
- The cartridge can be used inversely. Simply remove the cartridge and reverse it by turning it around.
- 3. Reassemble the housing as per the instructions.
- 4. Use as normal.

#### WHEN TO CHANGE FILTER

Cartridge life (approximate) is 6-12 months. Cartridge life is directly related to your water ed. Local water conditions may require more frequent

water conditions may require more trequent replacement.

REMINDER
_/



# ONE-YEAR LIMITED WARRANTY

CRYSTAL QUEST® warrants your CRYSTAL QUEST® Luxury Shower Power System for one year from the date of purchase against all defects in materials and workmanship when used in compliance with the manual. CRYSTAL QUEST® disclaims all implied warranties including, without limitation, warranties of merchantability and for a particular purpose. If for any reason the product proves to be defective within one year from the date of purchase, please call for assistance. This warranty gives you legal rights and you may have other legal rights, which vary from state to state. CRYSTAL QUEST® assumes no responsibility for incidental or consequential damages; for damages arising out of misuse of the product or the use of any unauthorized attachment. Some states do not allow the exclusion or limitation of implied warranties or incidental or consequential damages, so the above limitations or exclusions may not apply to you. Should service be required during or after the warranty period or should you have any questions regarding how to use your CRYSTAL QUEST® Luxury Shower Power System, contact our Technical Support department at warranty@crystalquest.com, Monday through Friday, 9 AM to 5 PM Eastern Standard Time.

#### KEEP THIS MANUAL FOR FUTURE REFERENCE AND UNIT MAINTENANCE

Online warranty information http://crystalquest.com/warranty.htm

Product design is subject to change without notice.

For further assistance, contact your Crystal Quest dealer or visit us at www.crystalquest.com

To view the latest edition of the Luxury Power Shower Guide, visit CrystalOuest.com

Please note all drawings, pictures, colors and sizes are approximate for illustrative purposes only and may not exactly resemble the end product.

CQE-SP-00800



COF-SP-00801



COF-SP-00802



COF-SP-00803



COF-RC-04045



