

# fiber options

# OH-RX-12G-ST Fiber SFP Data Sheet

## 12G SDI Single Channel Optical Receiver

- SDI multi-rate optical receiver for 12G-SDI, 6G-SDI, 3G-HDI and HD-SDI
- Support for SMPTE 2082, SMPTE 2081, SMPTE 424M, and SMPTE 292M
- Supports 1260 to 1620nm wavelengths
- For use with yellobrik, greenMachine, and Series 5000 product lines
- Pluggable and hot swappable
- Available in ST connectors (singlemode fiber only)
- MSA pinout
- Lead free and RoHS compliant

The OH-RX-12G-ST single channel optical receiver is an integrated plug in option for selected LYNX Technik products. This SFP module facilitates the conversion of optical signals to SDI electrical signals at ST-2082-1 (12G), ST-2081-1 (6G), ST-424 (3G) and ST-292 (HD).

The OH-RX-12G-ST module is a pluggable SFP with ST connector for use in LYNX products which provide an SFP slot. This module is paired with OH-TX-12G-ST single channel optical transmitter module to receive error-free signals up to a maximum distance of 10km\*\* over a single mode fiber at wavelength 1260nm to 1620nm.

A socket, or a "cage" is provided for the SFP in the supporting LYNX product for easy installation or upgrade. This SFP is hot swappable.



## Specifications

Parameter		Min	Typ	Max
Receiver Sensitivity (Measured with pathological pattern)	11.88 Gb/s	-	-	-10dBm
	5.94 Gbit/s	-	-	-10dBm
	2.97 Gbit/s	-	-	-14dBm
	1.485 Gbit/s	-	-	-14dBm
Wavelength		1260nm	-	1620nm
Overload		-2dBm	-	-
Loss of Signal De Assert		-	-	-10dBm
Loss of Signal Assert		-30dBm	-	-
Optical Hysteresis		0.5dB	2dB	-
Operating Temperature Range		0°C	-	70°C
Power Supply Voltage		3.1 VDC	3.3 VDC	3.5 VDC
Power Consumption		-	180ma	200mA
Humidity (non condensing)		-	-	90%

Country of manufacture: Taiwan

## Mechanical

Parameter	
Size (not including connector - typ)	57mm x 13.4mm x 12.4mm
Weight	50g
SFP Connector pinning	MSA
Fiber connections	ST connector

## Ordering Information

EAN / UPC	Model	Description
4250479327528	OH-RX-12G-ST	12G SDI Single Optical Receiver (RX) SFP Module

\*\* Distance is an approximation. Actual distances achieved can be longer or shorter depending on the type of fiber cable and accumulated optical losses in the fiber link. Determine link losses and perform optical budget calculations to ensure correct operation.

## WARNING

This SFP module is a Class 1 laser device which complies to IEC825 and FDA 21 CFR 1040.10 and 1040.11. The device must be operated within specified temperature and voltage limits. The optical ports of the module must always be terminated with an optical connector or a dust plug (dust plug supplied)



Rev 1.0 Specifications subject to change

**LYNXTechnik AG**

www.lynx-technik.com

**LYNX Technik AG**  
Brunnenweg 3  
D-64331 Weiterstadt  
Germany  
PH +49 (0) 6150 1817 0  
info@lynx-technik.com

**LYNX Technik Inc**  
26366 Ruether Ave.  
Santa Clarita, CA 91350  
USA  
PH +1 (661) 251 8600  
infousa@lynx-technik.com

**LYNX Technik Pte Ltd**  
114 Lavender Street  
#05-92 CTHub2  
Singapore, 338729  
PH +65 6702 5277  
infoasia@lynx-technik.com