



# Weighing Platform PCE-SD 300



**Weighing platform up to 300kg / resolution 0.1 kg / low construction height /**

**includes an access ramp / bidirectional RS-232 interface / totalizing function / piece counting function / tolerance weighing / optional 4-20 mA, 0-10 V or OC switching outputs**

The calibrated platform scale is ideal if you do not want to install a scale into the floor. Simply set up the platform scale in the hall, fix the platform scale and the access ramp with the fixing plates included in the scope of delivery, connect the control terminal to the socket and you can start weighing. An initial verification of the platform scale is carried out by us before dispatch, so the platform scale can be used immediately even in goods traffic that is subject to verification.

The platform scale has a low construction height of only approx. 5 cm and enables easy access even with heavy goods. An access ramp is included in the scope of delivery of the platform scales, the second access ramp can be ordered as an option. The display of the platform scale has a bracket that allows it to be mounted on the wall or on a table, a tripod for the platform scale is also optionally available. The functions of the platform scale are: piece counting function, a max. min. weighing, recipe weighing, percentage weighing, average weight determination, totalizing function, a tare weight memory and adjustable RS-232 interface.

- ▶ Piece counting function
- ▶ Percent % comparative weighing
- ▶ Filter (reaction time) adjustable
- ▶ Animal weighing function
- ▶ A tare value can be saved
- ▶ Tolerance determination weight min/ok/max
- ▶ Sum up several weighings
- ▶ Average weight determination
- ▶ Mixed recipe weighing
- ▶ Adjustable bidirectional RS-232 interface
- ▶ Line mode and EPL2 printer languages
- ▶ Adjustable automatic switch-off
- ▶ Gross / Net key on the display
- ▶ Menu freely adjustable
- ▶ Maintenance-free components
- ▶ Optional: USB, LAN or 4-20 mA

Subject to change

# Specifications

Model	Weighing range	Resolution	Min. *	Weight	Usable area
PCE-SD 300	300 kg	0.1 kg	2 kg	160 kg	860 x 1000 mm

**\*The minimum load is the load from which the calibration authority checks the accuracy. The verifiable drive-through scale also shows smaller weights, but these may not be used in legal transactions.**

Calibration	calibratable according to class M III (delivered calibrated)
Taring range	over the full weighing range
Settling time	<4 s
Display	LED with 20 mm digit height
Interface	RS-232 bidirectional Optional: USB / LAN / 4-20 mA / 0-10 V / OC
Calibration	external (not with the calibrated drive-through scale)
Operating temperature	-10°C ... +40°C
Power supply	~230V 50Hz 8VA (Schuko plug)
Protection	Display IP 54 / cells IP 67

# More information

**More product info**



**Similar products**



Subject to change