

PCW3000-A

Gas-Powered Pulling Winch GX35

PRO SERIES



**SINGLE LINE
PULLING FORCE**
1,600 LB / 700 KG



SPEED
33 FT/MIN / 10 M/MIN



WEIGHT
20 LB / 9.5 KG

+ INCLUDED with each winch

- 1 • Rope bag
- 2 • 50 m (164 ft) rope
- 3 • RopeWizer™ - The Easy Splice
- 4 • Single pulley
- 5 • Steel locking carabiners 2x
- 6 • Safety Hook with Latch
- 7 • 2 m (6 ½ ft) Polyester sling
- 8 • 2.5 m (8 ¼ ft) round polyester sling



	PCW3000
Series	Pro
Designed in	2012
Motor/Engine	POWERED by HONDA Honda GX35 4-stroke - 360° inclinable - air-cooled 1.0 kW - 1.3 HP @ 7,000 tr/min
Powered by	Gas
Drive/Clutch	Direct drive (no clutch)
Rope Retention System	No
Drum turns when motor/engine is idling	Yes
Pulling Capacity	
Standard drum (single line / double line)	Ø 3" (76 mm) : 1,600 lb / 3,200 lb - 700 kg / 1,400 kg
Optional drum (single line / double line)	No optional drum
Lifting Capacity	
Standard drum (single line / double line)	Not designed for lifting - See INDUSTRIAL SERIES winches
Optional drum (single line / double line)	No optional drum
Speed	
Standard drum	Ø 3" (76 mm) : 33'/min - 10 m/min
Optional drum	No optional drum
Weight	20 lb - 9.5 kg
Dimensions (overall)	13-3/4" x 11-3/8" x 10-1/4" - 35 cm x 28.9 cm x 26.1 cm
Gearbox	Aluminium alloy. Heat treated 3-stage helical & spur gears. Mounted on ball bearings. Oil bath lubrication.
Gear ratio	200:1
Brake	Anti-reversing roller clutch bearing
Rope	Low stretch double braided polyester
Length	Unlimited
Minimum diameter	Ø 3/8" (10 mm)
Maximum diameter	Ø 1/2" (13 mm)
Recommended diameter	Ø 3/8" (10 mm)
Warranty	Get 1 additional year of warranty if you register your product at www.portablewinch.com
Private use	5 years
Commercial use	1 year
Motor/Engine	Honda International Warranty
Certification	CE