

PCW5000-A

PRO SERIES

Gas-Powered Pulling Winch GXH50



**SINGLE LINE
PULLING FORCE**
2,200 LB / 1,000 KG



SPEED
40 FT/MIN / 12 M/MIN



WEIGHT
35 LB / 16 KG

+ INCLUDED with each winch

- 1 • Rope bag
- 2 • 50 m (164 ft) rope
- 3 • RopeWizer™ - The Easy Splice
- 4 • Single pulley
- 5 • Steel locking carabiners 2x
- 6 • Safety Hook with Latch
- 7 • 2 m (6 ½ ft) Polyester sling
- 8 • 2.5 m (8 ¼ ft) round polyester sling



	PCW5000
Series	Pro
Designed in	2003
Motor/Engine	POWERED by HONDA Honda GXH50 4-stroke air-cooled 1.6 kW - 2.1 HP @ 7,000 tr/min
Powered by	Gas
Drive/Clutch	Direct drive (no clutch)
Rope Retention System	No
Drum turns when motor/engine is idling	Yes
Pulling Capacity	
Standard drum (single line / double line)	Ø 2-1/4" (57 mm) : 2,200 lb / 4,400 lb - 1,000 kg / 2,000 kg
Optional drum (single line / double line)	Ø 3-3/8" (85 mm) : 1,600 lb / 3,200 lb - 700 kg / 1,400 kg
Lifting Capacity	
Standard drum (single line / double line)	Not designed for lifting - See INDUSTRIAL SERIES winches
Optional drum (single line / double line)	---
Speed	
Standard drum	Ø 2-1/4" (57 mm) : 40'/min - 12 m/min
Optional drum	Ø 3-3/8" (85 mm) : 60'/min - 18 m/min
Weight	35 lb - 16 kg
Dimensions (overall)	14-5/8" x 14-3/8" x 14-3/8" - 37.1 cm x 36.6 cm x 36.6 cm
Gearbox	Aluminium alloy. Heat treated 3-stage spur gears. Mounted on ball bearings. Oil bath lubrication.
Gear ratio	110:1
Brake	Anti-reversing roller clutch bearing
Rope	Low stretch double braided polyester
Length	Unlimited
Minimum diameter	Ø 3/8" (10 mm)
Maximum diameter	Ø 1/2" (13 mm)
Recommended diameter	Ø 1/2" (12 mm)
Warranty	Get 1 additional year of warranty if you register your product at www.portablewinch.com
Private use	5 years
Commercial use	1 year
Motor/Engine	Honda International Warranty
Certification	CE