AeGIS 7000P SERIES

MULTI-TENANTS TELEPHONE ENTRY SYSTEM



150-250 tenants and 150-250 codes

Single relay

Large LCD for easy reading

Postal lock ready

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

PART# 7250P

PART#· 7250FFP

Surface and Flush Mount.

Indoor or Outdoor

24 months warranty

FEATURES	PART#: 7150P (Surface Mount)	PART#: 7150FFP (Flush Mount)		PAR 1#: 7250P (Surface Mount)	PART#: 7250FFP (Flush Mount)
Input Power	12VAC included/12VDC	12VAC included/12VDC		12VAC included/12VDC	12VAC included/12VDC
Current Consumption	700 mA	700 mA		700 mA	700 mA
Operating Temperature	10°F to 145°F	10°F to 145°F		10°F to 145°F	10°F to 145°F
LiquidCrystal Display	16 x 1, 99mm x 13mm	16 x 1, 99mm x 13mm		16 x 1, 99mm x 13mm	16 x 1, 99mm x 13mm
Tenant Capacity	150	150		250	250
Code Capacity	150	150		250	250
Remote Access	yes	yes		yes	yes
Dry Contact Relay	1	1		1	1
Postal Lock Ready	yes	yes		yes	yes
Auxilary Input	1	1		1	1
Dimension (HWD)	10-13/16" x 8-5/8" x 3-3/4"	14-5/16" x 12-1/8" x 2-5/8" (Total Dimension) 11-1/8" x 8-11/16" x 2-5/8" (Inside Ring)		10-13/16" x 8-5/8" x 3-3/4"	14-5/16" x 12-1/8" x 2-5/8" (Total Dimension) 11-1/8" x 8-11/16" x 2-5/8" (Inside Ring)
		ACCES	SORIES		
UVPC: Analog color camera			UPM1L: 47" H Single arm pedestal		
USP1: AC and Telephone surge protector			UPM2: Dual vertical arm pedestal		
USP2L: Surge and Lightning protection			UPM5: Dual horizontal arm pedestal		
UBAT1: 12VDC 4.5 Ahr backup battery			UPM6L: 64" H Single arm pedestal		
IREXIT: Infrared exit switch			AHP5: Heater-pad		