

AeGIS 7000V SERIES

MULTI-TENANTS VOIP TELEPHONE ENTRY SYSTEM



250 tenants and 250 codes

Nominal monthly fees and taxes required, based on zipcode to activate the AATA2

Single relay

Large LCD for easy reading

Postal lock ready

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount.

Indoor or Outdoor. The AATA is indoor only.

24 months warranty

FEATURES	PART#: 7000V Surface Mount	PART#: 7000VFF Flush Mount
Input Power	12VAC included/12VDC	12VAC included/12VDC
Current Consumption	700 mA	700 mA
Operating Temperature	10°F to 145°F	10°F to 145°F
LiquidCrystal Display	16 x 1, 99mm x 13mm	16 x 1, 99mm x 13mm
Tenant Capacity	250	250
Code Capacity	250	250
AATA2 VOIP (included)	nominal monthly fees and taxes required	nominal monthly fees and taxes required
Remote Access	yes	yes
Dry Contact Relay	1	1
Postal Lock Ready	yes	yes
Auxiliary Input	1	1
Dimension (HWD)	10-13/16" x 8-5/8" x 3-3/4"	14-5/16" x 12-1/8" x 2-5/8" (Total Dimension) 11-1/8" x 8-11/16" x 2-5/8" (Inside Ring)

ACCESSORIES

UVPC: Analog color camera	UPM1L: 47" H Single arm pedestal
USP1: AC and Telephone surge protector	UPM2: Dual vertical arm pedestal
USP2L: Surge and Lightning protection	UPM5: Dual horizontal arm pedestal
UBAT1: 12VDC 4.5 Ahr backup battery	UPM6L: 64" H Single arm pedestal
IREXIT: Infrared exit switch	AHP5: Heater-pad