AeGIS 7000S SERIES

MULTI-TENANTS SLIM LINE TELEPHONE ENTRY SYSTEM



250 tenants, 600 cards and 600 codes

Programming via keypad

Time zones, holidays, temporary codes, hold open codes and auto unlock schedules

Nominal monthly fees and taxes required based on zip code to activate the AATA2 and SCWT are paid to Ooma.

Backlit Keypad

Remote Access unlocking door

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount. Indoor or Outdoor.

DA DT#. 7000CC

24 months warranty

FEATURES	PART#: 7000S		PART#: 7000SC		PART#: 7000SV
Input Power	12VAC included/12VDC		12VAC included/12VDC		12VAC included/12VDC
Current Consumption	700 mA		700 mA		700 mA
Operating Temperature	10°F to 145°F		10°F to 145°F		10°F to 145°F
LiquidCrystal Display	16 x 1, 99mm x 13mm		16 x 1, 99mm x 13mm		16 x 1, 99mm x 13mm
Tenant Capacity	250		250		250
Card Capacity	600, card reader is optional		600, card reader is optional		600, card reader is optional
Code Capacity	600		600		600
SCWT LTE CELLULAR (indoor)	optional		incl. Monthly fees and taxes		n/a
AATA2 (indoor)	optional (indoor only)		n/a		incl. Nominal monthly fees and taxes
26 Wiegand Input	1, card reader is optional		1, card reader is optional		1, card reader is optional
Auto Door Schedule	10		10		10
Time Zone	10		10		10
Holiday	16		16		16
Temporary card/code	10, max. 10 times		10, max. 10 times		10, max. 10 times
Unlock hold card/code	10		10		10
Door Sensor	2		2		2
Auxiliary Input	2		2		2
Slave Access Control RS-485	8, card reader, keypad or combo		8, card reader, keypad or combo		8, card reader, keypad or combo
Dry Contact Relay	1		1		1
Postal Lock Ready	yes		yes		yes
Auxilary Input	2		2		2
Dimension (HWD)	12-9/16" x 6-9/16" x 3-1/8"		12-9/16" x 6-9/16"	x 3-1/8"	12-9/16" x 6-9/16" x 3-1/8"
ACCESSORIES					
UVPC: Analog color camera UPM1L: 47" H S		UPM1L: 47" H Single a	rm pedestal	AHP5: Heater-pad	
USP1: AC and Telephone surge protector		UPM2: Dual vertical arm pedestal		IREXIT: Infrared exit switch	
USP2L: Surge and Lightning protection		UPM5: Dual horizontal arm pedestal			
UBAT1: 12VDC 4.5 Ahr backup battery		UPM6L: 64" H Single arm pedestal			

