

# AeGIS 8000P SERIES

## MULTI-TENANTS DIAL-UP MODEM TELEPHONE ENTRY SYSTEM



150-250 tenants and 150-250 codes

Single relay

Large LCD for easy reading

Postal lock ready

Built-in modem

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount.

Indoor or Outdoor

[24 months warranty](#)

FEATURES	PART#: 8250P	PART#: 8250FFP
Input Power	12VAC included/12VDC	12VAC included/12VDC
Current Consumption	700 mA	700 mA
Operating Temperature	10°F to 145°F	10°F to 145°F
LiquidCrystal Display	16 x 1, 99mm x 13mm	16 x 1, 99mm x 13mm
Tenant Capacity	250	250
Code Capacity	250	250
Modem	built-in	built-in
Event buffer	600	600
Dry Contact Relay	1	1
Postal Lock Ready	yes	yes
Auxiliary Input	1	1
Dimension (HWD)	10-13/16" x 8-5/8" x 3-3/4"	14-5/16" x 12-1/8" x 2-5/8" (Total Dimension) 11-1/8" x 8-11/16" x 2-5/8" (Inside Ring)

### ACCESSORIES

UVPC: Analog color camera	UPM1L: 47" H Single arm pedestal
USP1: AC and Telephone surge protector	UPM2: Dual vertical arm pedestal
USP2L: Surge and Lightning protection	UPM5: Dual horizontal arm pedestal
UBAT1: 12VDC 4.5 Ahr backup battery	UPM6L: 64" H Single arm pedestal
IREXIT: Infrared exit switch	AHP5: Heater-pad
AMDM: Dial-up modem for Windows	