





Single-Shot Relay Output

OPERATION

Voltage is continuously applied to the input. An external isolated switch controls the timer. When closed (momentary or maintained), the relay energizes and the delay period begins. Upon completion of the delay period, the relay de-energizes.



WIRING



SPECIFICATIONS

TIMING RANGES

Virtually unlimited. See page 77 for standard ranges available.

OUTPUT RATING DPDT, 10 A @ 250 VAC or 24 VDC, resistive;
211 VA @ 120 VAC, inductive

TIMING TOLERANCES Minimum Setting +0 – 20%

Maximum Setting ±10%;

REPEATABILITY 1% maximum; no first cycle effect

RESET TIMES Before Time Out 100 mSEC
After Time Out 50 mSEC

RECYCLE TIME 40 mSEC

SUPPLY VOLTAGE 24 or 120 VAC or VDC, 50/60 Hz; ±10%
(TUE Series available in 120 Volts only)

FALSE TRANSFER No

REVERSE POLARITY PROTECTED Yes

POWER CONSUMPTION 3 watts (approximately)

DUTY CYCLE Continuous


TEMPERATURE RATING Operate 32° to 131°F (0° to +55°C)
Storage -49° to 185°F (-45° to +85°C)

LIFE EXPECTANCY Mechanical 10 million operations (minimum)
Electrical 100,000 operations @ rated load

WEIGHT 4.5 oz.

For UL/CSA Approved version specify TUE Series of On-Delay Relay Output Timers.

DIMENSIONS (INCHES)



MODEL NUMBER

MODEL NUMBER	T		E		A		
SERIES							
Relay Output			D				
Relay Output with CSA			U*				
SUPPLY VOLTAGE							
24 VAC or DC				24			
110/120 VAC or DC				120			
TYPE OF OPERATION							
Knob Adjustable						K	
Lock Nut Adjustable						L	
Fixed						F	
External Resistor Adjustable						R**	
ENCLOSURE STYLE							
8-pin or 11-pin Round Plug-in							A
Blade Plug-in							B
DELAY PERIOD							
See page 82 for standard ranges available							

Example: TUE-120-AKA-900—Single Shot, 120 Volts AC or DC, knob adjustable from 9 to 900 seconds, 8-pin octal plug-in. UL recognized and CSA approved.

Notes:* The TUE series is offered in 120 Volts, octal plug-in (figure 23) style A enclosure only with optional types of operation "K", "L", or "F" CSA certified: File #LR40123

**TDE's using the "R" option are not UL Recognized. The "R" option is NOT offered in the TUE series or the style B enclosure.