

Model 6822-0 (49ST/Canada)  
UPC: 6964710682241

1 of 2



## FEATURES

- EASY PRIME™ Funnel design for quick and easy priming
- Hose kit included - 12' suction hose, 25' of discharge hose strainers and connectors
- Powerful Generac Pump - Can pump up to 158 gallons per minute
- Color coded suction and discharge ports to ensure the correct hose connections
- Durable design - Silicon Carbide Seal, Cast Iron Volute and Impeller
- Generac's 208cc OHV engine with splash lubrication provides a long engine life
- Low-oil shutdown automatically safeguards engine from damage

## SPECIFICATIONS

Engine Type	4 cycle/OHV
Engine Displacement (cc)	208
Start Type	Recoil Pull Start
Lubrication Method	Splash
Low Oil Shutdown Method	Low Level
Recommended Oil	10W-30 / SAE30
Fuel Capacity (gal.) L	(3) 11.5
Max Run Time	5hrs
Flow (GPM) LPM	(158) 598
Max Total Head (ft.) m	(108) 32.9
Max Suction Lift (ft.) m	(26) 7.9
Mechanical Seal Type	Silicon Carbide
Solid Handling (in.) mm	(0.25) 6.4
Suction Port (NPT)	2
Discharge Port (NPT)	2
Pump Housing	Aluminum
Impeller	Cast Iron
Volute	Cast Iron
Hose Kit Included	Yes
Discharge Hose Length (ft.) m	(25) 7.6
Suction Hose Length (ft.) m	(12) 3.7
Hose Connections	Metal Speed Nut
Strainer	Plastic
Wheel Kit	Yes
Country of Origin	China
Warranty	1 Year

Manual Part #	0K9077
Length (in) mm	(23.1) 587
Width (in) mm	(23.1) 588
Height (in) mm	(21.3) 541
Extended Length (in) mm	(37.8) 959
Unit Weight (lbs) kg	(36.2) 16.4
Carton Length (in) mm	(32.5) 825
Carton Width(in) mm	(18.5) 470
Carton Height (in) mm	(19.3) 490
Unit Weight (lbs) kg	(73.9) 33.5
Shipping Weight (lbs) kg	(98.5) 44.7

