

Model 7126-0 (49ST/Canada)
UPC: 696471071900

1 of 2



FEATURES

- EASY PRIME™ Funnel design for quick and easy priming
- High Performance Pump - Can pump up to 164 gallons per minute
- Color coded suction and discharge ports to ensure the correct hose connections
- Reinforced Fiberglass Pump - Ideal for clean water, chemical, herbicide, pesticide and fertilizer transfer
- Generac 223cc OHV engine with splash lubrication provides a long engine life

Specifications

| | |
|--------------------------|--------------------------------|
| Engine Type | 4 cycle/OHV |
| Engine Displacement (cc) | 223 |
| Start Type | Recoil Pull Start |
| Low Oil Shutdown Method | Low Level |
| Recommended Oil | 10W-30 / SAE30 |
| Fuel Capacity (gal/l) | 0.95/3.6 |
| Max Run Time | 1.4 hrs |
| Flow gpm/lpm | 164/746 |
| Max Total Head (ft/m) | 149/45.4 |
| Max Suction Lift (ft/m) | 26/7.9 |
| Mechanical Seal Type | Carbon Ceramic |
| Solid Handling (in) | 1/16 |
| Suction Port (NPT) | 2.0 |
| Discharge Port (NPT) | 2.0 |
| Pump Housing | Fiberglass Reinforced Nylon 66 |
| Impeller | Fiberglass Reinforced Nylon 66 |
| Volute | Fiberglass Reinforced Nylon 66 |

| | |
|------------------------------|-------------|
| Hose Kit Included | N/A |
| Discharge Hose Length (ft/m) | N/A |
| Suction Hose Length (ft/m) | N/A |
| Hose Connections | N/A |
| Strainer | N/A |
| Wheel Kit | N/A |
| Country of Origin | China |
| Warranty | 1 Year |
| Manual Part # | 10000014547 |
| Length (L) (in/mm) | 20.9/532 |
| Width (W) (in/mm) | 16.5/420 |
| Height (H) (in/mm) | 17.6/447 |
| Unit Weight (lbs/kg) | 52.4/23.8 |
| Carton Length (in/mm) | 21.6/549 |
| Carton Width (in/mm) | 17.1/435 |
| Carton Height (in/mm) | 18.5/470 |
| Shipping Weight (lbs/kg) | 56.9/25.8 |

