



**MORE
POWER**



**MORE
PRODUCTS**



**BETTER
ROI**

3" TRASH WATER PUMP

- **X-Frame - Fully Wrapped, Heavy Duty 11 Gauge Steel Frame**
Provides rugged durability and protects the hose connections from damage
- **Generac G-Force 265cc OHC Engine**
With low-oil shutdown
- **Large 2.9 Gallon Steel Fuel Tank**
With incorporated fuel gauge provides up to 4.3 hours of run time
- **Steel Lifting Pocket**
Designed for easier lifting and transportation on jobsites by crane or forklift
- **Engraving Plate**
Allows unit to be tagged /cataloged for use in contractor and rental fleets
- **Color-coded Suction and Discharge ports**
To ensure the correct hose connections. (Blue = Discharge; Green= Suction)
- **Easy Prime**
Custom funnel design for quick and easy priming
- **Durable Silicon Carbide Mechanical Seal**
For long life
- **Onboard Instructions**
With icons of key touch points make this pump easy to use



POWERED BY **GENERAC**
G-FORCE

BENEFITS

- **Built for the Jobsite:** Durable fully wrapped 11 gauge steel tube frame protects the engine and hose connections.
- **Easy Service:** Tool-free oil changes and commonly used service parts listed directly on unit.
- **Extended Runtimes:** Pump more than twice as long on one tank of fuel vs. the competition.*

*Compared to Honda WT30 3" Trash Pump which has a 1.5 hr max runtime at max discharge.

3" TRASH WATER PUMP



SPECIFICATIONS

MODEL NAME: XC3000P

MODEL NUMBER	G0077250 (50ST & CAN)	VOLUTE	Ductile Cast Iron
UPC	696471079692	HOSE KIT INCLUDED	N/A
ENGINE TYPE	4 cycle/OHC	DISCHARGE HOSE LENGTH (FT/M)	N/A
ENGINE DISPLACEMENT	265	SUCTION HOSE LENGTH (FT/M)	N/A
START TYPE	Recoil Pull Start	HOSE CONNECTIONS	N/A
LOW OIL SHUTDOWN METHOD	Low Level	STRAINER	Yes
RECOMMENDED OIL	10W-30 / SAE30	WHEEL KIT METHOD	N/A
FUEL CAPACITY (GAL/L)	2.9/10.9	COUNTRY OF ORIGIN	China
MAX RUN TIME	4.3 hrs	WARRANTY	3 Year
MAX FLOW GPM/LPM	350/1352	MANUAL PART #	10000016160
MAX TOTAL HEAD (FT/M)	90/27	LENGTH (L) (IN/MM)	31.5/800
MAX SUCTION LIFT (FT/M)	26/7.9	WIDTH (W) (IN/MM)	23.5/597
MECHANICAL SEAL TYPE	Silicon Carbide	HEIGHT (H) (IN/MM)	29.25/743
SOLID HANDLING (IN)	1.2	UNIT WEIGHT (LBS/KG)	163/74
SUCTION PORT (NPT)	3	CARTON LENGTH (IN/MM)	32.2/817
DISCHARGE PORT (NPT)	3	CARTON WIDTH (IN/MM)	24.1/612
PUMP HOUSING	Aluminum	CARTON HEIGHT (IN/MM)	25.3/642
IMPELLER	Ductile Cast Iron	SHIPPING WEIGHT (LBS/KG)	173/78.5

GENERAC
PRO



**DURABLE, RUGGED
PRODUCT DESIGN**



**THREE YEAR
LIMITED WARRANTY**



**24/7 • 365
CUSTOMER CARE**