

GC SERIES

ELECTRIC PRESSURE WASHERS

Enjoy the performance of a gas powered pressure washer with the convenience of an electric. The Generac GC2300W and GC2700W Electric Pressure Washers give you the power needed to tackle a variety of cleaning tasks. Ideal for windows, decks, patio furniture and other various cleaning tasks around the home, these units are a compact and easily transportable way to take high pressure cleaning power with you wherever you go.



GC2700W
Model G0088880 (50-State & Canada)
UPC: 696471083415

GENERAC®

HIGH PERFORMANCE MOTOR

Brushless motor for increased performance and durability

MAINTENANCE FREE PUMP WITH EASY-ACCESS HOSE CONNECTIONS

Prevents kneeling down on the ground

25FT HIGH PRESSURE HOSE

Non-marring, kink resistant hose will not leave marks on the job

AUTO-STOP SWITCH

Automatically shuts off the pump when trigger is not engaged to save energy and prolong pump life

ON-BOARD DETERGENT TANK

Large 1 gal. detergent tank for easy soap application

OVERSIZED NEVER-FLAT TIRES

Improved mobility on rugged terrain

RECOMMENDED USE



GC2300W

Model G0088870
UPC: 696471083408

GC2700W

Model G0088880
UPC: 696471083415

PRESSURE AND FLOW

| | | |
|-----------------------------------|----------|------------|
| Max Outlet Pressure (psi/bar) | 2300/159 | 2700/186.2 |
| Working Outlet Pressure (psi/bar) | 1700/117 | 2100/144.8 |
| Max Flow Rate (gpm)/(L/min) | 1.2/4.5 | |

ELECTRIC MOTOR

| | | |
|-------------|----------------------|--------------------|
| Motor Type | Brushless (Aluminum) | Brushless (Copper) |
| Motor Watts | 1600 | 1700 |
| Motor Volts | 120 | |
| Motor Amps | 13 | |

POWER CORD

| | | |
|---------------|--------------------|--|
| Type | Cat. No. 16-14 AWG | |
| Length (ft/m) | 35/10.67 | |
| GFCI Rating | AC 125V, 60Hz, 15A | |

PUMP

| | | |
|-------------------------------|-----------|--|
| Type | Axial Cam | |
| Pump Material | Aluminum | |
| Max Water Supply Temp (°F/°C) | 100/37.8 | |

HOSE

| | | |
|--------------------|----------------------|----------|
| Hose Type | PVC | |
| Length (ft/m) | 25/7.6 | |
| Diameter (in/mm) | 0.25/6.4 | |
| Rating (psi/bar) | 6380/440 | 8700/600 |
| Connectors | M22 Threaded | |
| Chemical Injection | Yes, 1 gal chem tank | |

NOZZLES

| | | |
|---------------------|------------------------|--|
| Nozzle Descriptions | (4) 0°, 15°, 25°, Soap | |
|---------------------|------------------------|--|

GUN & LANCE

| | | |
|----------------------------|----------------------|--|
| Gun Type | Ergonomic | |
| Gun to Lance Connection | M22 Threaded | |
| Gun to Hose Connection | Quick Change | |
| Lance Length (in/cm) | 29.5/75.0 | |
| Lance to Nozzle Connection | Quick Change | |
| Lance Material | Steel, chrome plated | |

FRAME & MISC.

| | | |
|--------------------|--------------------|--|
| Handle | Removable | |
| Frame Construction | Steel | |
| Wheels (in/cm) | 12/30.5 Never Flat | |