

Joist Tape

The Green Glue Noiseproofing Joist Tape is 100 linear feet long and available in widths of 1-7/16", 2-1/4", and 3". Select the width appropriate for your floor joists. The Joist Tape must cover the width of the joists to be effective.

Make sure all surfaces are free from dirt, ice, and water before applying the Noiseproofing Joist Tape.

Apply the Noiseproofing Joist Tape — **adhesive side down** — evenly to the top of each floor joist. This can be done by hand or using the Green Glue Joist Tape Applicator, pictured right.

Once placement of the Noiseproofing Joist Tape is complete, apply the sub-floor as normal to joists after being affixed.

Please note

The use of construction adhesive is **NOT** possible when securing the subfloor.

Joist Tape should be at least 50°F when applied for the adhesive to ensure the pressure sensitive adhesive will function.

Joist Tape is used to address squeaks when the subfloor rubs against the joists and does not provide other acoustical benefits.

Visit www.greengluecompany.com/FAQs for further information.



*Green Glue Joist Tape
Applicator*



Scan QR code to visit Green Glue FAQs.

DISCLAIMER: Because of the many installation variables beyond our control, Green Glue Company shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claims shall be deemed as waived unless made in writing to Green Glue Company within thirty (30) days from the date it was discovered, or reasonably should have been discovered.

Form # 1552 | © Saint-Gobain (November 2018) | Green Glue is a trademark of Saint-Gobain.