

# Sealant

## Prepare for Application

- Make sure the surfaces that are to be sealed are clean.
- Cut a 1/4" hole in the tip of the tube with a utility knife.
- Screw nozzle tightly over the tip of the tube and cut 1/4" hole in the tip of the nozzle.
- When the nozzle is cut, place the tube in a standard 28 ounce caulk gun to prepare for installation.



*Prepare for application*

## Apply Sealant

A very common application of Noiseproofing Sealant is filling 1/8" to 1/4" gaps where the drywall meets the floor and ceiling. Other applications include spaces around electrical outlets. The Sealant should not be used around pipes or copper based materials.

Apply 48 hours before painting to allow for drying time. Drywall tape and mud can be applied directly over Green Glue Noiseproofing Sealant.



*Apply Sealant*

For further information, watch our instructional video on how to use the Green Glue Noiseproofing Sealant by scanning the QR code below and visiting [www.greengluecompany.com/data-resources/videos](http://www.greengluecompany.com/data-resources/videos) or [www.greengluecompany.com/FAQs](http://www.greengluecompany.com/FAQs).



*Scan QR code to see how to apply Green Glue Noiseproofing Sealant.*

DISCLAIMER: Because of the many installation variables beyond our control, Green Glue Company shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claims shall be deemed as waived unless made in writing to Green Glue Company within thirty (30) days from the date it was discovered, or reasonably should have been discovered.