


AC2464



AS-Interface CompactLine module

CompactLineM12 4DI M12



Application	
Application	field installation
Electrical data	
Operating voltage [V]	26.5...31.6 DC
Max. current consumption from AS-i [mA]	250
Inputs / outputs	
Number of inputs and outputs	Number of digital inputs: 4
Inputs	
Number of digital inputs	4
Input circuit of digital inputs	PNP; (type 2 according to IEC 61131-2)
Sensor supply of the inputs	AS-i
Voltage supply [V]	20...30; (DC)
Max. total current rating of inputs [mA]	200
Input current limitation [mA]	15

AC2464



AS-Interface CompactLine module

CompactLineM12 4DI M12

Input current High	[mA]	6...10
Input current low	[mA]	0...2
Switching level high	[V]	> 11
Digital inputs protected against short circuits		yes

Operating conditions

Ambient temperature	[°C]	-25...80
Storage temperature	[°C]	-25...80
Max. relative air humidity	[%]	90; (non condensing)
Max. height above sea level	[m]	2000
Protection		IP 67; (when flat cables are used E7400x / E7401x)

Tests / approvals

EMC	EN 61000-6-2	
	EN 62026-2	
	EN 50581	
MTTF	[years]	382
UL approval	voltage supply	Class 2

AS-i classification

AS-i version	2.11; 3.0				
AS-i addressing	IR addressing possible				
Extended addressing mode	no				
AS-i master profile	M2; M3; M4				
AS-i profile	S-0.0.E				
AS-i I/O configuration	[hex]	0			
AS-i ID code	[hex]	0.E			
AS-i certificate	40501				
Data bits	Data bit	D0	D1	D2	D3
	Input	1	2	3	4
	Socket	I-1	I-2	I-3	I-4
	Pin	2+4	2+4	2+4	2+4

Mechanical data

Weight	[g]	301.5
Housing		AS-i voltage via M12 connector
Material		PA; Socket: brass nickel-plated; O-ring: FKM

Displays / operating elements

Display	Switching status	LED, yellow I1...I4
	Power	LED, green AS-i
	errors	LED, red

Electrical connection

Module connection	M12
-------------------	-----

Accessories

Accessories (optional)	stainless steel sleeve, for installation in case of high mechanical stress , E70402
------------------------	---

AC2464



AS-Interface CompactLine module

CompactLineM12 4DI M12

Remarks	
Remarks	Do not connect any of the following points to an external potential: I-, I+, I1, I2, I3, I4
Pack quantity	The connections are electrically connected with the AS-i cable. 1 pcs.

Electrical connection - AS-i


Connector: M12; coding: A



- 1 AS-i +
- 3 AS-i -

Electrical connection - Process connection

Connector: M12; coding: A



- 1 Sensor supply L+
- 2+4 Data input internally bridged 1
- 3 Sensor supply L-
- 5 functional earth