


EBT004



Wiring block

ZDO8H050VAS0015E19



Application	
System	Free from silicone; gold-plated contacts
Free from silicone	yes
Electrical data	
Operating voltage [V]	10...30 DC; (cULus - Class 2 source required)
Protection class	II
Max. current load per module/slot [A]	4
Max. current load total [A]	12
Operating conditions	
Ambient temperature [°C]	-25...70
Ambient temperature (moving) [°C]	-5...60

EBT004



Wiring block

ZDO8H050VAS0015E19

Protection	IP 67; IP 68
------------	--------------

Tests / approvals

UL approval	Enclosure type	Type 1
-------------	----------------	--------

Mechanical data

Weight	[g]	2875
Dimensions	[mm]	22 x 54 x 127
Material		housing: PA
Number of ports splitter box		8
Connector type		M12

Accessories

Items supplied	Protective caps: 2 labels: 8
----------------	---------------------------------

Remarks


Pack quantity	1 pcs.
---------------	--------

Electrical connection

Cable: 15 m, PVC, black, Ø 9.7 mm; 16 x 0.34 mm² + 3 x 1.0 mm²

Electrical connection - slot

Connector: 8 x M12; coding: A; Contacts: gold-plated; Tightening torque: 0.8...1.5 Nm



EBT004



Wiring block

ZDO8H050VAS0015E19

Connection

<u>BN</u>	1 (1...8)
<u>BU</u>	3 (1...8)
<u>GN/YE</u>	5 (1...8)
<u>GY/PK</u>	2 (1)
<u>RD/BU</u>	2 (2)
<u>WH/GN</u>	2 (3)
<u>BN/GN</u>	2 (4)
<u>WH/YE</u>	2 (5)
<u>YE/BN</u>	2 (6)
<u>WH/GY</u>	2 (7)
<u>GY/BN</u>	2 (8)
<u>WH</u>	4 (1)
<u>GN</u>	4 (2)
<u>YE</u>	4 (3)
<u>GY</u>	4 (4)
<u>PK</u>	4 (5)
<u>RD</u>	4 (6)
<u>BK</u>	4 (7)
<u>VT</u>	4 (8)

	Core colors :
BK =	black
BN =	brown
BU =	blue
GN =	green
GY =	grey
PK =	pink
RD =	red
VT =	lilac
WH =	white
YE =	yellow