


# OGP700



## Retro-reflective LASER sensor

OGPLFPKG/US100



1 Programming buttons



### Product characteristics

Type of light	red light
Laser protection class	1
Housing	Threaded type

### Application

System	polarization filter
Function principle	Retro-reflective sensor

### Electrical data

Operating voltage	[V]	10...36 DC
Current consumption	[mA]	15; (24 V)
Protection class		II
Reverse polarity protection		yes
Type of light		red light
Wave length	[nm]	655
Typ. lifetime	[h]	50000

### Outputs

Electrical design		PNP
Output function		light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	200
Switching frequency DC	[Hz]	2000
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes

### Monitoring range

Range referred to prismatic reflector	[m]	0.2...15; (Prismatic reflector Ø 80 E20005)
---------------------------------------	-----	---

# OGP700



## Retro-reflective LASER sensor

OGPLFPKG/US100

Factory setting	dark-on mode
Range adjustable	yes
Diameter of the smallest detectable object [mm]	3; (1 m; 15 m: 20)
Max. light spot diameter [mm]	78
Light spot dimensions refer to	at maximum range
Polarization filter available	yes

### Operating conditions

Ambient temperature [°C]	-10...60
Protection	IP 65; IP 67

### Tests / approvals

EMC	EN 60947-5-2	
Laser protection class	1	
Notes on laser protection	Caution:	Laser light
	laser class:	1
		EN / IEC60825-1:2007
		EN / IEC60825-1:2014
	Complies with 21 CFR 1040 except for deviations pursuant to Laser Notice No. 50, dated June 2007.	
MTTF [years]	600	

### Mechanical data

Weight [g]	63.5
Housing	Threaded type
Dimensions [mm]	M18 x 1 / L = 72
Thread designation	M18 x 1
Material	housing: stainless steel (1.4404 / 316L); operator interface: PA; sealing: EPDM; Pushbuttons: TPU (urethane)
Lens material	PMMA

### Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

### Accessories


Items supplied	lock nuts: 2
----------------	--------------

### Remarks

Remarks	cULus - Class 2 source required
Pack quantity	1 pcs.

### Electrical connection

Connector: 1 x M12; coding: A



# OGP700



## Retro-reflective LASER sensor

OGPLFPKG/US100

### Connection

