



AUDIO VIDEO SUPPLY

INNOVATIVE
HIGH DEFINITION SURVEILLANCE



OMNI
Resolution 960
Everyday

 **KPC-DNS102NUV**

Digital Day/Night, 750 TVL, Indoor, 3-Axis,
2.8-12mm, Dual Voltage



INNOVATIVE
HIGH DEFINITION SURVEILLANCE



OMNI
Resolution960
Everyday

KPC-DNS102NUV


Digital Day/Night, 750 TVL, Indoor, 3-Axis,
2.8-12mm, Dual Voltage

Features

- Superlative resolution of over 750 horizontal TV lines for amazing image quality
- 960H CCD with sensor sensitivity of .01 lux in low light without DSS boost
- Full motion color or digital day/night during low ambient light without ghosting
- Simple and easy to use OSD setup menu
 - Digital Wide Dynamic Range for proper contrast in challenging bright or unbalanced scene lighting conditions
 - Anti Color Roll for proper white balance independent of fluorescent or other types of illumination
 - Optional Back Light Compensation (BLC) and Highlight Compensation (HLC)
 - Adjustable 2D-Noise Reduction to increase low light picture clarity and conserve DVR HDD disk space
 - Privacy masking for 8 configurable zones
 - Lens shading compensation for even exposure out to the lens periphery
- 2.8~12mm 2 Megapixel Aspheric Varifocal DC Iris lens to capture the desired field of view
- Dual voltage (12VDC/24VAC) with Anti Color Roll
- Service Video output for convenient installation, and ease of service
- 3-Axis gimbal for convenient wall or ceiling mounting
- Choose between black and white color housing to blend or contrast with the décor

FCCE

Dimensions: Inches (mm)



AUDIO VIDEO SUPPLY

Digital
Day/Night

750
TVL

Digital
WDR

2.8-12
mm

3
Axis

OSD

DC12
Dual Voltage
AC24V

BLC
HLC

Low Light
Performance

Anti-CR

Service
Video

Imaging Device	1/3" 960H High Sensitivity CCD
Video Format	NTSC
Picture Elements	NTSC: 1020(H)x508(V)
Effective Picture Elements	NTSC: 976(H) x 494(V)
Horizontal Resolution	More than 750 TVL
Sensitivity	.01 lux native from sensor – no ghosting With lens: .1 lux
S/N Ratio	Over 50dB (AGC off)
Video Output	BNC 1.0V p-p 75Ω; video test point inside dome, cable supplied
Gamma Correction	0.45
Lens Type	2 Megapixel Aspheric Varifocal DC Iris 2.8~12mm F=1.6
Lens Positioning	3-axis flexible positioning for wall or ceiling mounting
Back Light Compensation	OFF/BLC/HLC Selectable
Auto Gain Control	Off/Low/Middle/High
Electronic Shutter	Auto; or 1/60, FLK, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/5000, 1/10000, 1/100000
White Balance	ATW/AWB/AWC->SET/Anti-Color Roll/Manual
Sync. Mode	Internal (plus Anti Color Roll White Balance option above)
Day & Night	Digital D/N control; Choose Auto, Color or B/W
OSD Menu	Multiple functions using 3-axis joystick
OSD Languages	English, Spanish, Portuguese, German, Russian, Japanese, Chinese, French
2D-DNR	On/Off (level adjustable)
Digital Wide Dynamic Range	On/Off (Level Adjustable)
Mirror	Off/On
Motion Detection	Off/On for 4 selectable zones (On screen indication)
Privacy Mask	Off/On for 8 selectable zones
Lens Shading Correction	Off/On with adjustable level and center
Other OSD Functions	Camera Title with position and Font Color; Image Contrast/Sharpness; CRT/LCD display optimization; Negative Image; DPC (Dead Pixel Compensation)
Power Source	12VDC/24VAC automatic
Power Consumption	12VDC:160mA max. / 24VAC:1.8W max.
Operating Temperature	5°F~140°F ; -15°C~60°C
Environmental	Indoor; up to 80%RH (non-condensing)
Mechanical	Three axis, twist-open dome; choice of black body (no suffix) and white body (W suffix)
Dimensions	5.31" (135mm) diameter, 3.82" (97mm) high
Weight	.76 lbs. / 343 grams
Certifications	CE / FCC RoHS