

# KVM-3216 16-Port PS/2-USB VGA KVM

## Product Images



## Short Description

- 16-port Rackmount USB-PS/2 KVM switch with OSD

- Cascadable up to 16 units using daisy-chain cable
- Daisy-chaining distance up to 30 M
- Port capacity scalable up to 256 PCs (16 x KVM-3216)
- USB and PS/2 interface support on both console and PC side
- Support Microsoft and Logitech standard 5-key mouse and compatibles
- Computer selection and operation using front-panel push buttons , keyboard hotkeys and OSD Menu
- Support for DOS, Windows 95/98/SE/ME/2000/XP/Vista/7, Linux, MacOS, etc.
- Numerical LED display and LED indicators for easy bank/port status monitoring
- Active Sync Replication for DDC emulation
- Keyboard/mouse emulation to ensure compatibility to all machines and operating systems
- Extensive support for USB keyboards and mice
- One controller per port to keep keyboard and mouse alive
- Enhanced PS/2 mouse reset hotkeys for non-PnP OS such as Win NT 4.0 and Linux
- Buzzer sound for hotkey and port switching confirmation
- Autoscan period programmable 10 ~ 95 through OSD Menu option
- Password protection
- Auto-logout timeout support
- High VGA resolution 2048 x 1536
- PC side emulation module upgradable
- Firmware upgrad

## Description

---

The LevelOne KVM-3216 16-port combo KVM switch enables users to control and manage a server farm or computers connected to the KVM switch with either the local console or remote console port. Local Console The KVM-3216 Combo KVM Switch is easy to connect to a keyboard and mouse with a VGA monitor through the local console port. This enables a user to control systems connected to the KVM switch directly. Remote Console In order to make use of the remote control feature.

## Additional Information

---

Color	Black
EAN	4015867229392
Model Number	KVM-3216
Display Type	VGA
Installation	Rack Mount
Approval and Compliance	CE/FCC
Operating humidity	0% RH ~ 85% RH
Operating temperature	0°C ~ 40°C
Storage humidity	0% RH ~ 90% RH
Storage temperature	-10°C ~ 70°C
Package Contents	KVM-3216 Universal Power Adapter User Manual Upgrade Cable Daisy Chain Cable End Point Terminator
Dimensions (W x D x H)	410x165x44.5
Product weight (kg)	2.2
Indicators	Power Port LED x8
Resolution	2048 x 1536