

---

# POI-5002W60 Gigabit PoE Injector, 802.3 af/at/bt, 60W

## Product Images

---



## Short Description

---

Auto-detection and protection of non-standard PoE devices

IEEE 802.3af/at/bt PoE compliant to simplify deployment and installation

Total PoE power budget: 60W,

## Description

---

POI-5002W60 is a single port, high-power 60W PoE PSE solution for remote PoE PD devices. Generating up to 60W through 8 pins, POI-5002 supplies remote power for new applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras, lighting, panel display for digital signage and video-phones. It complies to IEEE 802.3bt PoE standards to deliver 60W on both end-point and midspan pairs with a total power of 60W PoE output. It can work with 10/100Base-T networking devices and emerging 1000Base-T devices such as Wi-MAX and wireless IEEE 802.11n access points.

## Additional Information

---

Color	Black
EAN	4015867223253
Model Number	POI-5002W60
Features	1-port GigE Ultra PoE Injector
Injector Port Type	Single Port
Data rate	Gigabit Ethernet
Grade	Commercial
Operating humidity	0% RH ~ 95% RH
Operating temperature	0°C ~ 40°C
Package Contents	POI-5002W60 Power Cord
Dimensions (W x D x H)	180 x 71 x 37 mm
Product weight (kg)	0,53
Data rate	10/100/1000Mbps
Indicators	Power, Mode A, Mode B
Mount	Wall mount
Pin assignment and polarity	1/2 (+), 3/6 (-) & 4/5 (+), 7/8 (-)
Power Output	60W
Standards	IEEE 802.3at/af/bt IEEE 802.3 10-BASE-T IEEE 802.3u 100-BASE-TX IEEE 802.3ab 1000BASE-T